


Customer Information Sheet

DRAWING No.: S1951-46R SHEET 3 OF 3 IF IN DOUBT - ASK (C) NOT TO SCALE THIRD ANGLE PROJECTION ALL DIMENSIONS IN mm


SI941-46R DEFLECTION FROM ABOVE




RECOMMENDED WORKING HEIGHT
OF 6.65mm = 0.50mm DEFLECTION,
MINIMUM FORCE OF 1.2N

6.05

MINIMUM RECOMMENDED HEIGHT OF 6.05mm = 1.10mm DELFECTION SI941-46R DEFLECTION FROM FRONT



RECOMMENDED WORKING LENGTH
OF 9.09mm = 0.40mm DEFLECTION
MINIMUM FORCE OF 1.2N



MINIMUM RECOMMENDED LENGTH OF 8.49mm = 1.00mm DEFLECTION

COMPONENT SPECIFICATION:
MATERIAL = BERYLLIUM COPPER

FINISH = 3µ 100% TIN OVER 2µ NICKEL

CURRENT RATING = 7A MAX

SB I 09.08.13 12181

NAME ISS. DATE C/NOTE

APPROVED: S.BENNETT

CHECKED: M.PLESTED

DRAWN: S.BENNETT

CUSTOMER REF.:

ASSEMBLY DRG:

HARWIN

www.harwin.com technical@harwin.com THIS DRAWING AND ANY
INFORMATION OR DESCRIPTIVE
MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT
PROPERTY OF THE HARWIN
GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED
OR USED FOR MANUFACTURING,
TENDERING OR FOR ANY

OTHER PURPOSE WITHOUT

THEIR WRITTEN PERMISSION

X. = ±1mm X.X = ±0.25mm X.XX = ±0.10mm X.XXX = ±0.01mm

TOLERANCES

(.XXX = ±0.01mr ANGLES = ±5° UNLESS STATED MATERIAL:

SEE ABOVE

FINISH: SEE ABOVE

S/AREA: mm²

TITLE:

MULTI-DIRECTIONAL SHIELD FINGER IN TAPE AND REEL

DRAWING NUMBER:

S1951-46R

SHT 3 OF