	PART NO.		REVISIONS							
multicomp		ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
mancomp	BMC2S-RED	-	1.0	RELEASED	SAN	15/11/13	B ER	15/11/13	ER	15/11/13
	Operatir Max. Ele	ficatior g Temper ectrical Ra Electrical laterial	ature Ra ting	ange : -20°C to +125°C : 600V Max. : Polycarbonate (PC) : Stainless Steel : Red						
415 22 22 22 22 22 22 22 22 22 22 22 22 22						Access and and a second se				

SCALE 14

Dimensions: Millimetre

1.9

15.9

34.9

36.4

Part Number Table

Description	Part Number				
Battery Modular Connectors	BMC2S-RED				

www.element14.com www.farnell.com www.newark.com

- H-											
L	back are being to day supprise in the interface of the construction of the constructio	TOLERANCES:	DRAWN BY:	DATE:	DRAWING TITLE:						
Т		UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE	SAN	15/11/13		Housing, Red, 50A, 2Pole					
			CHECKED BY:	DATE:	SIZE	DWG NO.		ELECTRONIC FILE		REV	
			ER	15/11/13	A4	A4 BMC2S-RED-03			BMC2S-RED		
L			APPROVED BY:	DATE:	SCALE: NTS						
L	not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.		ER	15/11/13	SCAL	E: NIS	0.0.M.: mn	0.M.: mm (inch) SHEET: 1 of		1	