


PART NO.

MC000755

REVISIONS								
ECN#	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	1.0	RELEASED	DO	01/04/14	ER	01/04/14	ER	01/04/14



Dimensions: Millimetres

Specifications:

AWG Maximum Electric Current

Wire Range : 4AWG (25mm²) **Surface Treatment** : Tin Plated Thickness : 1.5mm

Part Number Table

Description	Part Number
Crimp Terminal, Tubular Lug, 25-M10, Flared	MC000755

www.element14.com www.farnell.com www.newark.com

Important Notice: This data sheet and its contents (the "Information") belong to the members of the TOLERANCES: Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces al data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

UNLESS OTHERWISI
SPECIFIED,
DIMENSIONS ARE
FOR REFERENCE
PURPOSES ONLY.

DATE:
01/04/14
DATE:
01/04/14
Y: DATE:
01/04/14

	DRAWING TITLE:							
4	Non-Insulated Copper Tubular Lug, Flared							
	SIZE	DWG NO.		ELECTRO	REV			
4	A4	MC000755-	01	MC000755		1.0		
1	SCALE: NTS		U.O.M.: mm		SHEET: 1 of 1			