








NOTE


- THIS PRODUCT IS PACKAGED IN TRAY. (49pcs/TRAY)
- BLEMISH AND HIT MARK CAN BE OCCURED THROUGH OUT THE MANUFACTURING PROCESS WHICH DOSEN'T AFFECT QUALITY LEVEL. ALSO, BLACK SPOT COULD BE OBSERVED ON THE SURFACE OF HOUSING.
- FOR THE CONTACT NO., ADJACENT TWO PAIRS OF LEADS PLACED BACK-TO-BACK (4 LEADS IN TOTAL) COMPOSE ONE LINE.
- MISALIGNMENT ABSORBING RANGE: ± 0.3 mm max.
- THE DIMENSION IN PARENTHESES ARE FOR REFERENCES.
- LOT NO. IS INDICATED AT EITHER ONE OF THE POSITION AS SHOWN.

2	COPPER ALLOY	CONTACT AREA:GOLD-PLATING 0.1 μm			4	POLYSTYRENE					
		LEAD AREA:TIN-PLATING 1.0 μm				3	PHOSPHOR BRONZE	TIN-PLATING 3.0 μm			
		UNDER PLATING:NICKEL 1.0 μm						UNDER PLATING:NICKEL 1.0 μm			
1	POLYAMIDE	BLACK UL94V-0									
NO.	MATERIAL	FINISH , REMARKS			NO.	MATERIAL	FINISH , REMARKS				
UNITS mm				SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED : HS. OKAWA			13. 03. 07	DRAWING NO.		EDC3-347264-00			
		CHECED : KI. HIROKAWA			13. 03. 07	PART NO.		FX30B-2P-3. 81DSA30			
		DESIGNED : DK. AIMOTO			13. 03. 07	CODE NO.		CL570-3300-2-00			
		DRAWN : DK. AIMOTO			13. 03. 07						
										1/2	


RECOMMENDED HOLE PATTERN DIMENSION OF PCB(5:1)
(CONNECTOR MOUNTING SIDE, PCB THICKNESS: t=1.6mm)



1 DRAWING FOR PACKAGING(1:2)



A(1:1)



HRS

DRAWING NO.	EDC3-347264-00
PART NO.	FX30B-2P-3.81DSA30
CODE NO.	CL570-3300-2-00

2/2