


SIZE	PART NO.	REV.
B	2943666631	5



ELECTRICAL SPECIFICATIONS

Impedance (Ohms)		
10 MHz	50 MHz	100 MHz
400 Min.	800 Min.	550 Min.

Bold numbers are in millimeters,light numbers are in inches**

NOTES:

- 1 - CHIPS, CRACKS, AND APPEARANCE TO MEET FAIR-RITE VISUAL INSPECTION CRITERIA FOR GENERIC MULTI-HOLE WOUND BEADS.
- 2 - IMPEDANCE MEASURED ON A HP4193A, USING A 04193-87001 PROBE KIT.
- 3 - WIRE MEETS SOLDERABILITY SPECIFICATION WHEN TESTED PER SOP# ELC-57.
- 4 - PART MEETS FAIR-RITE PRODUCTS CORP SOP# ELC-55, FOR THERMAL SHOCK RESISTANCE.
- 5 - WIRE LOOPS SHOULD BE UNIFORM IN LENGTH.
- 6 - PACKAGING: THIS PART IS BULK PACKED. 200 PIECES/BAG, 1 BAG/BOX, 20 BOXES/F2 = 4,000 PIECES/CARTON.

5	B-8225	UPDATED NOTE No. 3, ADDED NOTE No. 5: THERMAL SHOCK		D.S.	10-05-06		
4	B-6569	WIRE PART NUMBER WAS 0199017501		D.S.	03-14-05		
3	B-6175	REMOVE "LF" DESIGNATION		J.Q.	11-30-04		
2	B-4760	ADDED FR# 2943666631LF TO PRINT		D.S.	12-01-03		
1	B- 122	ADDED NOTES TO PRINT		J.J.	01-17-01		
REV.	ECN	DESCRIPTION			DRFT	DATE	
REVISIONS							
APPLICABLE SPECS		DRAWING CLASS	 FAIR-RITE PRODUCTS CORP.				
		MATERIAL					
Tolerances Unless Otherwise Indicated		FR# 43	TITLE			WOUND BEAD	
3PL 2PL FRACT ANGLE		FINISH	DRAWN BY J. JANUS	DATE 06-27-1997	SIZE	PART NO.	REV.
			CHKD BY		B	2943666631	5
		APPRVD BY		SCALE: NONE		SHEET 1 OF 1	