













- NOTE
- THIS PRODUCT IS PACKAGED IN TRAY. (35pcs/TRAY)
 - BLEMISH AND HIT MARK CAN BE OCCURED THROUGH OUT THE MANUFACTURING PROCESS WHICH DOESN'T AFFECT QUALITY LEVEL. ALSO, BLACK SPOT COULD BE OBSERVED ON THE SURFACE OF HOUSING.
 - FOR THE CONTACT NO., ADJACENT TWO PAIRS OF LEADS PLACED BACK-TO-BACK (4 LEADS IN TOTAL) COMPOSE ONE LINE.
 - MISALIGNMENT ABSORBING RANGE: ± 0.3mm max.
 - THE DIMENSION IN PARENTHESES ARE FOR REFERENCES.
 - LOT NO. IS INDICATED AT EITHER ONE OF THE POSITION AS SHOWN.

2	COPPER ALLOY	CONTACT AREA:GOLD-PLATING 0.1 μm		4	POLYSTYRENE	
		LEAD AREA:TIN-PLATING 1.0 μm				
		UNDER PLATING:NICKEL 1.0 μm				
1	POLYAMIDE	BLACK UL94V-0		3	PHOSPHOR BRONZE	TIN-PLATING 3.0 μm
						UNDER PLATING:NICKEL 1.0 μm
NO.	MATERIAL	FINISH , REMARKS		NO.	MATERIAL	FINISH , REMARKS


UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED : HS. OKAWA		13.03.13	DRAWING NO.	EDC3-347275-00		
		CHECED : KI. HIROKAWA		13.03.12	PART NO.	FX30B-5S-3.81DSA		
		DESIGNED : DK. AIMOTO		13.03.11	CODE NO.	CL570-3503-0-00		
		DRAWN : DK. AIMOTO		13.03.11				

 1/2


RECOMMENDED HOLE PATTERN DIMENSION OF PCB(5:1)
(CONNECTOR MOUNTING SIDE, PCB THICKNESS: t=1.6mm)



1 DRAWING FOR PACKAGING(1:2)



A(1:1)



HRS

DRAWING NO.	EDC3-347275-00
PART NO.	FX30B-5S-3.81DSA
CODE NO.	CL570-3503-0-00

2/2