



NOTES ① THE RECOMMENDED CLAMP TORQUE, REF. NO. ⑤ AND ⑪ : 2 N·m.
 REF. NO. ⑪ SHALL BE TIGHTENED BY TORQUE AFTER CLAMPED UNTIL IT TOUCHES THE SURFACE B.
 2 ONE EXAMPLE OF THE ROTATION OF REF. NO. ①, ⑤ AND ⑪ ARE SHOWN.

| 6 | POLYAMIDE | | | | |
|-----|------------|-------------------------------|-----|-----------------|----------------------------|
| 5 | BRASS | MATTE FINISH NICKEL PLATED | 11 | BRASS | MATTE FINISH NICKEL PLATED |
| 4 | BRASS | GOLD PLATING 0.2μm min. | 10 | POLYAMIDE | |
| 3 | BRASS | NICKEL UNDER PLATING 2μm min. | 9 | BRASS | MATTE FINISH NICKEL PLATED |
| 2 | POLYAMIDE | (BLUE) | 8 | STEEL | NICKEL PLATING |
| 1 | ZINC ALLOY | MATTE FINISH NICKEL PLATED | 7 | STAINLESS STEEL | |
| NO. | MATERIAL | FINISH , REMARKS | NO. | MATERIAL | FINISH , REMARKS |

| | | | | | | | |
|---------------------------|--|------------------------|------------|--|-------------------------|----------------------|--------------------|
| UNITS mm | | SCALE 2 : 1 | COUNT 1 | DESCRIPTION OF REVISIONS DIS-C-002608 | DESIGNED TP. KOMATSU | CHECKED EJ. KUNII | DATE 12. 05. 29 |
| HIROSE ELECTRIC CO., LTD. | | APPROVED : MO. SATOH | 05. 10. 24 | DRAWING NO. | EDC4-007760-73 | | |
| | | CHECKED : EJ. KUNII | 05. 10. 21 | PART NO. | HR10-10P-12P(73) | | |
| | | DESIGNED : DS. MATSUNE | 05. 10. 19 | CODE NO. | CL110-0025-7-73 | | |
| | | DRAWN : DS. MATSUNE | 05. 10. 19 | | 1/1 | | |