





- NOTES
- 1 THE RECOMMENDED CLAMP TORQUE OF REF.NO. ① TO BE 3 N · m.
LOCTITE 271, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF.NO. ① FROM LOOSENING.
 - 2 THE RECOMMENDED CLAMP TORQUE OF REF.NO. ④ TO BE 0.3 TO 0.35 N · m.
 - 3 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER, DEPENDING ON THE CABLE STRUCTURE. PLEASE CONFIRM BEFORE THE USE.

2	BRASS	NICKEL PLATING		4	STAINLESS STEEL	M3×0.5×8		
1	BRASS	CHROME PLATING		3	SILICONE RUBBER	(BLACK)		
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS		
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED : SU. OBARA		11. 07. 06	DRAWING NO.	EDC4-110598-72		
		CHECKED : HY. KISHI		11. 07. 06	PART NO.	JR13WCC-8(72)		
		DESIGNED : HK. NAMAI		11. 07. 06	CODE NO.	CL114-2049-1-72		
		DRAWN : HK. NAMAI		11. 07. 06	 1			