








Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case that the application demands a high level of reliability, such as automotive,
please contact a company representative for further information.



APPLICATION DIAGRAM




RECOMMENDED PATTERN(5:1)
(RECOMMENDED BOARD THICKNESS t=1.6mm)



NOTES 1 :IMMERSION DEPTH INTO POTTING SOLUTION:6.5mm

1	PBT	WHITE, UL94V-0	3	HIPS	TRAY
			2	BRASS	SURFACE:TIN PLATED 1μm min UNDER PLATING:NICKEL PLATED 0.5μm min
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	
HIROSE ELECTRIC CO., LTD.		APPROVED : KI. AKIYAMA	12.07.24	DRAWING NO.	EDC3-338421-01
		CHECKED : HK. UMEHARA	12.07.24	PART NO.	DF33C-3P-3.3DSA(24)
		DESIGNED : HT. SATO	12.07.24	CODE NO.	CL676-1132-5-24
		DRAWN : MI. SAKIMURA	12.07.24	1/2	

Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case that the application demands a high level of reliability, such as automotive,
please contact a company representative for further information.



NOTES 2 :MINIMUM UNIT OF PURCHASE SHALL BE THE QUANTITY
OF CONNECTORS IN TRAY.(95 PIECES)

HRS	DRAWING NO.	EDC3-338421-01	
	PART NO.	DF33C-3P-3.3DSA(24)	
	CODE NO.	CL676-1132-5-24	△2/2