






Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case that the application demands a high level of reliability, such as automotive,
please contact a company representative for further information.

TO
PCK



RECOMMENDED LAND PATTERN DIMENSION OF PCB (MOUNTING SIDE)





FIG.1(5:1)



- NOTES 1 LEAD CO-PLANARITY SHALL BE 0.15 MAX.
2 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.
3 IN CASE OF THE AUTOMATED MOUNTING, RECOMMENDED HOLE DIAMETER OF BOSS IS SHOWN IN FIG.1.

3	BRASS	TIN-PLATING	2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.2μ m min.
1	PPS	LIGHT BROWN (UL94V-0)			LEAD AREA:TIN-PLATING 2μ m min.
					UNDER PLATING:NICKEL 2μ m min.
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
CODE NO.(OLD) CL			DRAWN	DESIGNED	CHECKED
			A.SUZUKAWA	K.Nakamura	K.Ogawa
			06.03.07	06.03.07	06.03.07
DRAWING NO. EDC3-082754-21			PART NO. FX2-32P-1.27SVL(71)		
SCALE 2 : 1			CODE NO. CL572-2052-0-71		
UNITS mm			1/1		
HRS HIROSE ELECTRIC CO., LTD					