



- NOTES 1 CONTACT AREA:GOLD PLATING 0.2µm min.  
TERMINAL AREA:GOLD FLASH.  
UNDER PLATING:NICKEL 2µm min.  
2 CHECK THAT THE O-RING IS PROPERLY SET AT THE GROOVE OF  
THE DEVICE.  
WHILE MOUNTING THE CONNECTOR,MAKE SURE THAT  
THE O-RING IS NOT CAUGHT.

2	POLYPHENYLENE SULFIDE (BLACK) UL94V-0			
1	ZINC ALLOY	BLACK CHROMATE TREATMENT (Cr3)	3	COPPER ALLOY
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL
				FINISH . REMARKS
UNITS mm		SCALE 2 : 1	COUNT △	DESCRIPTION OF REVISIONS
				DESIGNED
				CHECKED
				DATE
				APPROVED : MO. SATOH 07. 04. 05
				CHECED : MO. SATOH 07. 04. 05
				DESIGNED : DS. MATSUNE 07. 04. 05
				DRAWN : MK. SATO 07. 03. 30
				DRAWING NO. EDC3-114744-00
				PART NO. HR34B-12WRA-10P
				CODE NO. CL134-0016-6-00
				1/1