

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

SHELL: ZINC ALLOY, NICKEL PLATED
COUPLING RING: ALUMINUM ALLOY, NICKEL PLATED
INSERT AND RETAINING RING: THERMOPLASTIC
SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: THREADED HOUSING; REDUCED DIA. SEAL
- 3. SPECIFICATIONS:
 - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
 - 3.4 MOISTURE RESISTANCE: IP67&IP69K (MATED CONDITION).
 - 3.5 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDM04-18-20S* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.





CONTACT SIZE	MIN. INSUL O.D.	MAX. INSUL O.D.	TYPICAL WIRE RANGE	CURRENT RATING	
20	1.02 mm (.040 in)	2.41 mm (.095 in)	16-22 AWG	7.5 AMPS	
16	1.35 mm (.053 in)	3.05 mm (.120 in)	14-20 AWG	13 AMPS	

REVISIONS							
REV	ECO	DESCRIPTION	DATE	BY	APPR		
A1	-	RELEASE NEW DRAWING	17/OCT/18	BROOK	TOMMY		
A2	-	ADD MORE MATERIAL NOTES	24/OCT/18	ROOKIE	TOMMY		

PLUG, 18 SZ 20 PIN, RD, WIDE

AHDM06-18-20PR





	AHDM0	6-18-20PR					
	PART N	UMBER			DESCRIPTION	ITEM	
QUANTITY		1	MAT	ERI	ALS LIST		
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 2 PL DEC ±0.08 3) Note reference = X		SIGNATURES		DATE	Amphopol		
		DRAWN:	ROOKIE	24/OCT/18	Amphenol		
		CHECKED:	ORION	24/OCT/18	Sine Systems - www.amphenol-sine.com		
		ENGINEER:			44724 Morley Drive		
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	24/OCT/18	Clinton Township, MI 48036		
PROCESS SPECIFICATIONS:		CUSTOMER:			PLUG, 18 SZ 20 PIN, RD, WIDE TH	HD	
		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT ON DEMAN		FEATURES, RMANCE DATA OPERTY OF DN. NO RIGHTS JED. ALL	B C- AHDM06-18-20PR	REVISION A2	
				S.	SCALE: NONE SHEET 1	of 1	