

- | | |
|--|--|
| | |
| | |

A	7	2	MOUNTING SCREW, M2.5 X
	6	XX	SCREW, M2 X 0.4 X 5.2 (
	6	XX	SCREW, M2 X 0.4 X 5.2 (
	5	XX	RISEING CAGE CLAMP
	4	XX	GOLD PLATED TERMINAL (-
	3	XX	STANDARD TERMINAL
	2	1	PLUG BASE
	1	1	INSULATOR BODY
	ITEM	QTY.	DESCRIPTION

	6	XX	SCREW, M2 X 0.4 X 5.2 (
	6	XX	SCREW, M2 X 0.4 X 5.2 (
A	5	XX	RISEING CAGE CLAMP
	4	XX	GOLD PLATED TERMINAL (-
	3	XX	STANDARD TERMINAL
	2	I	PLUG BASE
	1	I	INSULATOR BODY
	ITEM	QTY.	DESCRIPTION

10	9	8	7	6	5	4	3	2	SD-39900-004																																																																																																																																																																								
<table><tr><td>ASSEMBLY MATERIAL NO. (STANDARD)</td><td>ASSEMBLY MATERIAL NO. (-G30 OPTION)</td><td>ASSEMBLY MATERIAL NO. (-10AV OPT.)</td><td>NUMBER OF CIRCUITS "XX"</td><td>DIM. "A"</td><td>DIM. "B"</td><td>DIM. "C"</td><td>DIM. "D"</td></tr><tr><td>399001702</td><td>399011702</td><td></td><td>02</td><td>18.2 (.72)</td><td>3.8 (.15)</td><td>12.8 (.50)</td><td>8.8 (.35)</td></tr><tr><td>399001703</td><td>399011703</td><td>399021703</td><td>03</td><td>22.0 (.87)</td><td>7.6 (.30)</td><td>16.6 (.65)</td><td>12.6 (.50)</td></tr><tr><td>399001704</td><td>399011704</td><td></td><td>04</td><td>25.8 (1.02)</td><td>11.4 (.45)</td><td>20.4 (.80)</td><td>16.4 (.65)</td></tr><tr><td>399001705</td><td>399011705</td><td></td><td>05</td><td>29.6 (1.17)</td><td>15.2 (.60)</td><td>24.2 (.95)</td><td>20.2 (.80)</td></tr><tr><td>399001706</td><td>399011706</td><td></td><td>06</td><td>33.4 (1.32)</td><td>19.1 (.75)</td><td>28.0 (1.10)</td><td>24.1 (.95)</td></tr><tr><td>399001707</td><td>399011707</td><td></td><td>07</td><td>37.2 (1.47)</td><td>22.9 (.90)</td><td>31.9 (1.25)</td><td>27.9 (1.10)</td></tr><tr><td>399001708</td><td>399011708</td><td></td><td>08</td><td>41.0 (1.62)</td><td>26.7 (1.05)</td><td>35.7 (1.40)</td><td>31.7 (1.25)</td></tr><tr><td>399001709</td><td>399011709</td><td></td><td>09</td><td>44.9 (1.77)</td><td>30.5 (1.20)</td><td>39.5 (1.55)</td><td>35.5 (1.40)</td></tr><tr><td>399001710</td><td>399011710</td><td></td><td>10</td><td>48.7 (1.92)</td><td>34.3 (1.35)</td><td>43.3 (1.70)</td><td>39.3 (1.55)</td></tr><tr><td>399001711</td><td>399011711</td><td></td><td>11</td><td>52.5 (2.07)</td><td>38.1 (1.50)</td><td>47.1 (1.85)</td><td>43.1 (1.70)</td></tr><tr><td>399001712</td><td>399011712</td><td></td><td>12</td><td>56.3 (2.22)</td><td>41.9 (1.65)</td><td>50.9 (2.00)</td><td>46.9 (1.85)</td></tr><tr><td>399001713</td><td>399011713</td><td></td><td>13</td><td>60.1 (2.37)</td><td>45.7 (1.80)</td><td>54.7 (2.15)</td><td>50.7 (2.00)</td></tr><tr><td>399001714</td><td>399011714</td><td></td><td>14</td><td>63.9 (2.52)</td><td>49.5 (1.95)</td><td>58.5 (2.30)</td><td>54.5 (2.15)</td></tr><tr><td>399001715</td><td>399011715</td><td></td><td>15</td><td>67.7 (2.67)</td><td>53.3 (2.10)</td><td>62.3 (2.45)</td><td>58.3 (2.30)</td></tr><tr><td>399001716</td><td>399011716</td><td></td><td>16</td><td>71.5 (2.82)</td><td>57.2 (2.25)</td><td>66.1 (2.60)</td><td>62.2 (2.45)</td></tr><tr><td>399001717</td><td>399011717</td><td></td><td>17</td><td>75.3 (2.97)</td><td>61.0 (2.40)</td><td>70.0 (2.75)</td><td>66.0 (2.60)</td></tr><tr><td>399001718</td><td>399011718</td><td></td><td>18</td><td>79.1 (3.12)</td><td>64.8 (2.55)</td><td>73.8 (2.90)</td><td>69.8 (2.75)</td></tr><tr><td>399001719</td><td>399011719</td><td></td><td>19</td><td>83.0 (3.27)</td><td>68.6 (2.70)</td><td>77.6 (3.05)</td><td>73.6 (2.90)</td></tr><tr><td>399001720</td><td>399011720</td><td></td><td>20</td><td>86.8 (3.42)</td><td>72.4 (2.85)</td><td>81.4 (3.20)</td><td>77.4 (3.05)</td></tr><tr><td>399001721</td><td>399011721</td><td></td><td>21</td><td>90.6 (3.57)</td><td>76.2 (3.00)</td><td>85.2 (3.35)</td><td>81.2 (3.20)</td></tr></table>										ASSEMBLY MATERIAL NO. (STANDARD)	ASSEMBLY MATERIAL NO. (-G30 OPTION)	ASSEMBLY MATERIAL NO. (-10AV OPT.)	NUMBER OF CIRCUITS "XX"	DIM. "A"	DIM. "B"	DIM. "C"	DIM. "D"	399001702	399011702		02	18.2 (.72)	3.8 (.15)	12.8 (.50)	8.8 (.35)	399001703	399011703	399021703	03	22.0 (.87)	7.6 (.30)	16.6 (.65)	12.6 (.50)	399001704	399011704		04	25.8 (1.02)	11.4 (.45)	20.4 (.80)	16.4 (.65)	399001705	399011705		05	29.6 (1.17)	15.2 (.60)	24.2 (.95)	20.2 (.80)	399001706	399011706		06	33.4 (1.32)	19.1 (.75)	28.0 (1.10)	24.1 (.95)	399001707	399011707		07	37.2 (1.47)	22.9 (.90)	31.9 (1.25)	27.9 (1.10)	399001708	399011708		08	41.0 (1.62)	26.7 (1.05)	35.7 (1.40)	31.7 (1.25)	399001709	399011709		09	44.9 (1.77)	30.5 (1.20)	39.5 (1.55)	35.5 (1.40)	399001710	399011710		10	48.7 (1.92)	34.3 (1.35)	43.3 (1.70)	39.3 (1.55)	399001711	399011711		11	52.5 (2.07)	38.1 (1.50)	47.1 (1.85)	43.1 (1.70)	399001712	399011712		12	56.3 (2.22)	41.9 (1.65)	50.9 (2.00)	46.9 (1.85)	399001713	399011713		13	60.1 (2.37)	45.7 (1.80)	54.7 (2.15)	50.7 (2.00)	399001714	399011714		14	63.9 (2.52)	49.5 (1.95)	58.5 (2.30)	54.5 (2.15)	399001715	399011715		15	67.7 (2.67)	53.3 (2.10)	62.3 (2.45)	58.3 (2.30)	399001716	399011716		16	71.5 (2.82)	57.2 (2.25)	66.1 (2.60)	62.2 (2.45)	399001717	399011717		17	75.3 (2.97)	61.0 (2.40)	70.0 (2.75)	66.0 (2.60)	399001718	399011718		18	79.1 (3.12)	64.8 (2.55)	73.8 (2.90)	69.8 (2.75)	399001719	399011719		19	83.0 (3.27)	68.6 (2.70)	77.6 (3.05)	73.6 (2.90)	399001720	399011720		20	86.8 (3.42)	72.4 (2.85)	81.4 (3.20)	77.4 (3.05)	399001721	399011721		21	90.6 (3.57)	76.2 (3.00)	85.2 (3.35)	81.2 (3.20)
ASSEMBLY MATERIAL NO. (STANDARD)	ASSEMBLY MATERIAL NO. (-G30 OPTION)	ASSEMBLY MATERIAL NO. (-10AV OPT.)	NUMBER OF CIRCUITS "XX"	DIM. "A"	DIM. "B"	DIM. "C"	DIM. "D"																																																																																																																																																																										
399001702	399011702		02	18.2 (.72)	3.8 (.15)	12.8 (.50)	8.8 (.35)																																																																																																																																																																										
399001703	399011703	399021703	03	22.0 (.87)	7.6 (.30)	16.6 (.65)	12.6 (.50)																																																																																																																																																																										
399001704	399011704		04	25.8 (1.02)	11.4 (.45)	20.4 (.80)	16.4 (.65)																																																																																																																																																																										
399001705	399011705		05	29.6 (1.17)	15.2 (.60)	24.2 (.95)	20.2 (.80)																																																																																																																																																																										
399001706	399011706		06	33.4 (1.32)	19.1 (.75)	28.0 (1.10)	24.1 (.95)																																																																																																																																																																										
399001707	399011707		07	37.2 (1.47)	22.9 (.90)	31.9 (1.25)	27.9 (1.10)																																																																																																																																																																										
399001708	399011708		08	41.0 (1.62)	26.7 (1.05)	35.7 (1.40)	31.7 (1.25)																																																																																																																																																																										
399001709	399011709		09	44.9 (1.77)	30.5 (1.20)	39.5 (1.55)	35.5 (1.40)																																																																																																																																																																										
399001710	399011710		10	48.7 (1.92)	34.3 (1.35)	43.3 (1.70)	39.3 (1.55)																																																																																																																																																																										
399001711	399011711		11	52.5 (2.07)	38.1 (1.50)	47.1 (1.85)	43.1 (1.70)																																																																																																																																																																										
399001712	399011712		12	56.3 (2.22)	41.9 (1.65)	50.9 (2.00)	46.9 (1.85)																																																																																																																																																																										
399001713	399011713		13	60.1 (2.37)	45.7 (1.80)	54.7 (2.15)	50.7 (2.00)																																																																																																																																																																										
399001714	399011714		14	63.9 (2.52)	49.5 (1.95)	58.5 (2.30)	54.5 (2.15)																																																																																																																																																																										
399001715	399011715		15	67.7 (2.67)	53.3 (2.10)	62.3 (2.45)	58.3 (2.30)																																																																																																																																																																										
399001716	399011716		16	71.5 (2.82)	57.2 (2.25)	66.1 (2.60)	62.2 (2.45)																																																																																																																																																																										
399001717	399011717		17	75.3 (2.97)	61.0 (2.40)	70.0 (2.75)	66.0 (2.60)																																																																																																																																																																										
399001718	399011718		18	79.1 (3.12)	64.8 (2.55)	73.8 (2.90)	69.8 (2.75)																																																																																																																																																																										
399001719	399011719		19	83.0 (3.27)	68.6 (2.70)	77.6 (3.05)	73.6 (2.90)																																																																																																																																																																										
399001720	399011720		20	86.8 (3.42)	72.4 (2.85)	81.4 (3.20)	77.4 (3.05)																																																																																																																																																																										
399001721	399011721		21	90.6 (3.57)	76.2 (3.00)	85.2 (3.35)	81.2 (3.20)																																																																																																																																																																										
<table><tr><td rowspan="2">EC NO. SEE SHEET 1 DRWN: CH K APPR: A</td><td rowspan="2">DESCRIPTION REV</td><td>QUALITY SYMBOLS MAJOR CRITICAL SPC</td><td>GENERAL TOLERANCES: (UNLESS SPECIFIED) mmINCH 4 PLACES 3 PLACES 2 PLACES 1 PLACE ANGULAR: ±2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</td><td>SCALE - DRAWN BY & DATE C. YORK 08-07-03 CHECKED BY & DATE APPROVED BY & DATE CAD FILENAME 9068XX01</td><td>DESIGN UNITS ☐ mm ☒ INCH</td><td>THIRD ANGLE PROJECTION</td><td>TITLE: VERTICAL PLUGGABLE SR BTS W/MTG RWE ASSY, 3.81 (.150) CENTERS MOLEX INCORPORATED</td><td>PROJECT NO. - DIMENSIONS: ☒ mm INCH ☐ INCH mm ☐ mm ONLY</td><td>- SHT REVISE ON CAD ONLY</td><td>- REV</td></tr><tr><td colspan="4">THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.</td><td colspan="2">SHEET NO. 2 OF 2 SIZE B</td></tr></table>										EC NO. SEE SHEET 1 DRWN: CH K APPR: A	DESCRIPTION REV	QUALITY SYMBOLS MAJOR CRITICAL SPC	GENERAL TOLERANCES: (UNLESS SPECIFIED) mmINCH 4 PLACES 3 PLACES 2 PLACES 1 PLACE ANGULAR: ±2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SCALE - DRAWN BY & DATE C. YORK 08-07-03 CHECKED BY & DATE APPROVED BY & DATE CAD FILENAME 9068XX01	DESIGN UNITS ☐ mm ☒ INCH	THIRD ANGLE PROJECTION	TITLE: VERTICAL PLUGGABLE SR BTS W/MTG RWE ASSY, 3.81 (.150) CENTERS MOLEX INCORPORATED	PROJECT NO. - DIMENSIONS: ☒ mm INCH ☐ INCH mm ☐ mm ONLY	- SHT REVISE ON CAD ONLY	- REV	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.				SHEET NO. 2 OF 2 SIZE B																																																																																																																																																								
EC NO. SEE SHEET 1 DRWN: CH K APPR: A	DESCRIPTION REV	QUALITY SYMBOLS MAJOR CRITICAL SPC	GENERAL TOLERANCES: (UNLESS SPECIFIED) mmINCH 4 PLACES 3 PLACES 2 PLACES 1 PLACE ANGULAR: ±2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SCALE - DRAWN BY & DATE C. YORK 08-07-03 CHECKED BY & DATE APPROVED BY & DATE CAD FILENAME 9068XX01	DESIGN UNITS ☐ mm ☒ INCH	THIRD ANGLE PROJECTION	TITLE: VERTICAL PLUGGABLE SR BTS W/MTG RWE ASSY, 3.81 (.150) CENTERS MOLEX INCORPORATED	PROJECT NO. - DIMENSIONS: ☒ mm INCH ☐ INCH mm ☐ mm ONLY	- SHT REVISE ON CAD ONLY			- REV																																																																																																																																																																					
		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.				SHEET NO. 2 OF 2 SIZE B																																																																																																																																																																											
10	9	8	7	6	5	4	3	2	1																																																																																																																																																																								