

CUSTOMER DRAWING

3800S 175/-3

REV

PART NUMBER	MATERIAL	FINISH
3800S 75A-3	.020 THICK BRASS	PRETINNED
3800S 175AB-3	.020 THICK BRASS	NONE
3800S 175AD-3	.020 THICK BRASS	POST-TIN

NOTES:

- I. CMA RANGE: 1600 TO 5000
- 2. FOR PIGTAIL SPLICES USED IN A BENCH APPLICATOR, ADD SUFFIX "PP" TO PART NUMBER (i.e. 3800S 175A-3PP), SEE FIGURE I FOR REELING.
- 3. FOR THROUGH SPLICES USED IN A BENCH APPLICATOR, THE PART NUMBER REMAINS THE SAME AS IN THE TABLE (i.e. 3800S 175A-3). SEE FIGURE 2 FOR REELING.
- 4. FOR PIGTAIL AND THROUGH SPLICES USED IN A SLIM-LINE AIR PRESS, THE PART NUMBER REMAINS THE SAME AS IN THE TABLE (i.e. 3800S 175A-3). SEE FIGURE 2 FOR REELING.
- 5. PAPER INTERLEAVING ADDED TO REDUCE TANGLING IN REELS.

ARK-LES UNCONTROLLED

