
REVISIONS							
REV	ECO	DESCRIPTION	DATE	BY	APPR		
A1	-	RELEASED DRAWING	Feb-14-19	White	Tommy		



## NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC **SEAL: SILICONE RUBBER** 

2. SPECIFICATIONS:

2.1 CURRENT RATING: 100 AMPS

2.2 VOLTAGE RATING: 1000 V AC/DC

2.3 OPERATING TEMPERATURE: -55°C TO +125°C

2.4 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 3000 VOLTS AC.

2.5 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.


2.6 MOISTURE RESISTANCE: IP67 AND IP69K IN THE MATED CONDITION.


2.7 MATING CYCLE DURABILITY: 100 CYCLES


2.8 RoHS COMPLIANT

- 3. SUITABLE CONTACTS:4# CONTACTS
- 4. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 5. CONTACT SIZE AND REAR SEAL WIRE RANGE:

CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	
SIZE	O.D.	O.D.	WIRE RANGE	
4	7.1 mm	7.4 mm	6 AWG	







	SEE PART NUMBER CHART							
	PART N	NUMBER			Amphenol Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036			
QUANTITY	MATERIALS LIST							
UNLESS OTHERWISE SPECIFIED  1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 Pi, DEC \$4.03 2 Pi, DEC \$4.05 3 Pi, DEC \$4.05 3) Note reference =		SIGN	ATURES	S DATE	- 1	\ ~~	nhanal	
		DRAWN:	White	Feb-14-19	Amphenoi			
		CHECKED:	Tod	Feb-14-19	Sine Systems - www.amphenol-sine.com			
		ENGINEER:						
		APPROVAL:	Tommy	Feb-14-19	Clinton Township, MI 48036			
		CUSTOMER:			A <sup>-</sup>	SERIE	S.PLUG.1 PIN.SOCKET	
		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL						
				B C	DWG NO:	ATHD06-1-4S	A1	
				SCALE: NONE		sнеет <b>1</b> оғ	1	

AT SERIES, PLUG, 1 PIN, SOCKET