




COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
1	DIS-C-000585	T.K	E.K	07.07.27					




B DETAIL OF MOUNTING GUIDE





A - A




PANEL CUTOUT
(t = 0.7 TO 2)







B



PCB LAYOUT
(INDICATES THE SIDE OF THE SURFACE TO WHICH DIP POSTS ARE INSERTED.)

NOTE ① THE RECOMMENDED CLAMP TORQUE, REF. NO. ⑥ : 2N · m.
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. ⑥ FOR LOOSENING.

3	POLYBUTYLENE TEREPHTHALATE (BLACK)	UL94V-0	6	BRASS	NICKEL PLATING
2	STAINLESS STEEL		5	PHOSPHOR BRONZE	NICKEL PLATING
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED	4	PHOSPHOR BRONZE	SILVER PLATING 2μ m min.
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS

CODE NO. (OLD) CL	DRAWN M.SATO '07 04 11	DESIGNED T.HORII '07 04 11	CHECKED E.KUNII '07 04 11	APPROVED M.SATO '07 04 11	RELEASED
----------------------	------------------------------	----------------------------------	---------------------------------	---------------------------------	----------

DRAWING NO. EDC4-042756-71	PART NO. HR10G-10R-12SB(71)	CODE NO. CL110-1809-2-71
 HIROSE ELECTRIC CO., LTD.		1/1