



Notes

- 1 The recommended tighten torque of Ref.No. ⑩ to be 0.2 to 0.3N·m.
Adhesive loctite 243, HENKEL JAPAN or equivalent is recommended to prevent Ref.No. ⑩ from loosening.
- 2 Pre-Assembled rotation examples of Ref.No. ① and No. ⑥ are shown.

5	Brass	Nickel plating	10	Brass	Nickel plating	M2.6×0.45×2		
4	Diallyl phthalate	(Black) UL94V-0	9	Phosphor bronze	Nickel plating			
3	Diallyl phthalate	(Black) UL94V-0	8	Brass	Nickel plating	JIS B 1101 M2×0.4×10		
2	Copper alloy	Silver plating 2μm min.	7	Brass	Nickel plating			
1	Brass	Nickel plating	6	Brass	Nickel plating			
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS		
UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
HIROSE ELECTRIC CO., LTD.		APPROVED		·SU. OBARA	16. 01. 20	DRAWING NO. EDC-028024-71-00		
		CHECKED		·HY. KOBAYASHI	16. 01. 19	PART NO. RM15TP-2SA(71)		
		DESIGNED		·HR. SATO	16. 01. 19	CODE NO. CL109-0845-0-71		
		DRAWN		·HR. SATO	16. 01. 19			