




Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



CONNECTOR APPLICATED SECTIONAL VIEW (SECTION A-A)
FDB-25P NOT STRAIN-RELIEF



3	STEEL	SURFACE PLATING : NICKEL 0.8μm min. UNDER PLATING : COPPER 2μm min.	6	STEEL	SURFACE PLATING : NICKEL 0.8μm min. UNDER PLATING : COPPER 2μm min.
2	STEEL	SURFACE PLATING : NICKEL 3μm min. UNDER PLATING : COPPER 2μm min.	5	STEEL	SURFACE PLATING : NICKEL 0.8μm min. UNDER PLATING : COPPER 2μm min.
1	ABS	UL94HB, COLOR : GRAY	4	STEEL	SURFACE PLATING : NICKEL 0.8μm min. UNDER PLATING : COPPER 2μm min.
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS

UNITS mm		SCALE 1 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED : YH. ENAMI		08.11.29	DRAWING NO.	EDC3-008602-01		
		CHECKED : HO. MIWA		08.11.29	PART NO.	HDB-CTF<50>		
		DESIGNED : HN. ANDO		08.11.29	CODE NO.	CL211-0139-0-50		
		DRAWN : HN. ANDO		08.11.29	 1 / 1			