



Notes) 1. Assembling should be done as per drawing.

- △ 2. The cable clamping power and the turning force, etc. are different according to the structure of the cable, and use it, please after it confirms it beforehand.

3	PBT	(Black) UL94V-0	6	Steel	Nickel plating	Tapping screw M2×4
2	Zink alloy	Nickel plating	5	Soft ployvinyl chloride	(Black) UL94V-0	
1	Zink alloy	Nickel plating	4	Copper alloy	Tin plating	
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS	

UNITS mm	SCALE 2 : 1	COUNT △ 2	DESCRIPTION OF REVISIONS DIS-C-00003067	DESIGNED TY. TAKAHASHI	CHECKED EJ. KUNII	DATE 20190402
HRS HIROSE ELECTRIC CO., LTD.			APPROVED : TM. AKIYAMA 20051201	DRAWING NO. EDC-043932-71-71		
			CHECKED : TM. AKIYAMA 20051201	PART NO. HR212-10P-8P<71>		
			DESIGNED : HS. KAWASHIMA 20051119	CODE NO. CL112-4001-3-71		
			DRAWN : HS. KAWASHIMA 20051119	△ 1/1		