



CUSTOMER DRAWING

REVISIONS



SYM	ECN	DESCRIPTION	DATE	APPROVED
SEE SHEET 1				



View of inserted card



Switch Posotion



Micro SD Express Card

Micro SD Express Card Pin Function Definition:
(微型内存卡Pin功能定义)

PIN NO.	FUNCTION
1	DATA LINE(BIT 2)
2	CARD DETECT/DATA LINE(BIT 3)
3	COMMAND RESPONSE
4	SUPPLY VOLTAGE(3.3V)
5	CLOCK
6	SUPPLY VOLTAGE GROUND
7	DATA LINE(BIT 0)
8	DATA LINE(BIT 1)
9	SUPPLY VOLTAGE(1.8V)
10	SUPPLY VOLTAGE GROUND
11	PCLE TRANSMIT LANE~TX+ (HOST TO CARD)
12	PCLE TRANSMIT LANE~TX- (HOST TO CARD)
13	SUPPLY VOLTAGE GROUND
14	PCLE RECEIVE LANE~RX-(HOST TO CARD)
15	PCLE RECEIVE LANE~RX+(HOST TO CARD)
16	SUPPLY VOLTAGE GROUND
17	SUPPLY VOLTAGE(1.2V)
SW	Detect whether the card is inserted
DE	Detect whether the card is inserted

UNLESS OTHERWISE SPECIFIED TOLERANCES		APPROVAL	DATE	Amphenol Amphenol East Asia Limited	
.X	+/-	DRAWN	09/08/20		
.XX	+/-	CHECKED	09/08/20	TITLE Customer Drawing For Micro SD experss 7.0	
.XXX	+/-	ANGLES			
FRACTIONS		REMOVE SHARP EDGES	ANGLE OF PROJECTION	SIZE A3	
SEE NOTES		DIMENSIONS			
U.S.		INCHES		SCALE	NONE
(METRIC)		(MM)		SHEET	2 OF 2