

Ha-VIS eCon 3026 BT-AT1-SPE



Image is for illustration purposes only. Please refer to product description.

Part number	24 05 002 6400
Specification	Ha-VIS eCon 3026 BT-AT1-SPE
HARTING eCatalogue	https://b2b.harting.com/24050026400

Identification

Series	Ha-VIS eCon 3000
Identification	Single Pair Ethernet (SPE)
Element	Industrial Ethernet Switches
Type of Ethernet	Fast Ethernet

Version

Total number of ports	8
Fixing	35 mm DIN rail acc. to EN 60715
Signal contact	No
Field of application	Indoor usage
Pack contents	Pluggable screw contact for power supply Assembly instructions

Termination data

Nominal voltage	24 V DC 48 V DC
Permissible voltage	16.8 ... 60 V DC
Surge protection	Yes
Operating current	96 mA @ 24 V DC 51 mA @ 48 V DC
Supply circuit	SELV (Circuit Breaker 10 A)
Starting current	<1.3 A @ 24 V DC <2.2 A @ 48 V DC
Overcurrent protection	2 A At input



Pushing Performance
Since 1945

Termination data

Power consumption	<2.3 W @ 24 V DC
Termination method	Pluggable screw contact
Number of contacts	3
Conductor cross-section	0.08 ... 2.5 mm ²
Conductor cross-section	AWG 28 ... AWG 12
Pinout	+ / - / FE
Reverse polarity proof	Yes

Technical characteristics

Pollution degree	2
Overvoltage category	II (400 ≤ CTI < 600)
Operating temperature	-40 ... +70 °C
Storage temperature	-40 ... +85 °C
Relative humidity	0 ... 95 % Non-condensing (operation) 0 ... 95 % Non-condensing (storage/transport)
Air pressure	≥795 hPa ≈ 2000 m
Degree of protection acc. to IEC 60529	IP30 mated condition

Ethernet ports copper

100 Mbit/s (RJ45-Ports)	2
Fast-Ethernet Ports 100 Mbit/s (RJ45-Ports) Transmission standard: 100BASE-TX Transmission physics: Twisted Pair Cat. 5 Transmission length: 100 m Data rate: 100 Mbit/s Auto-negotiation: yes Auto-polarity: yes Auto-MDI(X): yes	
Transmission standard	100BASE-T
Auto-polarity	Yes
Auto-MDI(X)	Yes
Transmission physics	Twisted Pair Cat. 5
Transmission length	100 m

Ethernet ports SPE

100 Mbit/s (SPE-Ports)	6
------------------------	---



Pushing Performance
Since 1945

Ethernet ports SPE

Single-Pair-Ethernet Port 100 Mbit/s (SPE-T1-Ports)

Transmission standard: 100BASE-T1

Transmission physics: Twisted Pair Cat. 5 6

Transmission length: 15 m

Data rate: 100 Mbit/s

Configuration Master-Slave via DIP-Switch

Transmission standard	(100BASE-T1)
Transmission physics	Twisted Pair 2 wires
Data rate	100 Mbit/s
Transmission length	15 m
Configuration Master-Slave	via DIP-Switch

Material properties

Material (hood/housing)	Aluminium (anodised) Stainless steel
Length	64.5 mm
Width	33 mm
Height	130 mm
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

Specifications and approvals

Specifications	EN 55032 emission standard EN 55035 EMC Interference immunity EN 61000-4-2 Electrostatic discharge (ESD) EN 61000-4-3 Electromagnetic field EN 61000-4-4 Rapid transients (burst) EN 61000-4-5 Surge voltages EN 61000-4-6 conducted disturbances EN 61000-6-4 emission standard IEC 60068-2-6 Vibration (sinusoidal)
CE	Yes
Approvals	on request
PROFINET	Yes



Pushing Performance
Since 1945

Specifications and approvals

FCC	Yes
-----	-----

Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85176200
GTIN	5713140195141
eCl@ss	19170130 Network switch (general application)