NOTES:

1. MATERIALS AND FINISHES:
   BODY, REAR BODY, COUPLING NUT, CAP
   & INNER FERRULE - BRASS, NICKEL PLATING
   CONTACT - BeCu, GOLD PLATING
   INSULATOR - PTFE, NATURAL
   RETAINING RING - PHOSPHOR BRONZE, NICKEL PLATING
   GASKET - SILICONE RUBBER, RED

2. ELECTRICAL:
   A. IMPEDANCE: 50 OHM
   B. FREQUENCY RANGE: DC - 7.1 GHz
   C. VSWR: 1.30 MAX. DC - 3 GHz
      1.40 MAX. 3 - 6 GHz
   D. DIELECTRIC WITHSTANDING VOLTAGE: 500 VRMS, MIN.

3. MECHANICAL:
   A. DURABILITY: 500 CYCLES MIN.
   B. TEMPERATURE RANGE: -65°C TO +165°C

4. PACKAGING:
   A. QUANTITY: SINGLE PACK
   B. MARKING: PACKAGING TO BE MARKED
      "AMPHENOL RF, 31-6982 AND DATE CODE"
   C. CAP AND INNER FERRULE ARE PACKAGED LOOSE.

5. CABLE ASSEMBLY INSTRUCTIONS:
   A. TRIM CABLE AS SHOWN (TWO STAGE TRIM).
   B. INSERT CABLE THROUGH INNER FERRULE AND PEEL BRAID BACK, OVER INNER FERRULE
   C. INSERT CABLE INTO THE CONNECTOR.
   D. SOLDER CONTACT TO CABLE CENTER CONDUCTOR.
   E. CRIMP BODY OVER INNER FERRULE USING 0.105" HEX.
   F. PRESS CAP FLUSH.

6. SHOWS CABLE ENTRY DIMENSIONS.

REVISIONS				
REV	DESCRIPTION	DATE	ECN	BY
A	RELEASE TO MFG.	24-SEP-24	17177	SH



SCALE 1.500





RECOMMENDED CABLE STRIPPING DIMENSIONS (TRIM 1)



RECOMMENDED CABLE STRIPPING DIMENSIONS (TRIM 2)



CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

THIRD ANGLE PROJ.

REFERENCE

EAR# 10195

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE METRIC [INCHES] AND TOLERANCES ARE:
<0.5mm = ±0.05mm [<0.020 = ±0.002]
>0.5 - 6mm = ±0.1mm [>0.020 - 0.236 = ±0.004]
>6.00 - 30mm = ±0.2mm [>0.236 - 1.181 = ±0.008]
>30.00 - 120mm = ±0.3mm [>1.181 - 4.725 = ±0.012]
ANGLES = ±1°

MATERIAL: SEE NOTES

TITLE: RP TNC RA PLUG FOR 1.13 MM CABLE

ENGR.1	ENGR.2	DATE
R KARTHIK	JACK LIANG	22-FEB-21

SHEET NO. 2 OF 2

SCALE: 6.5:1.0

Amphenol RF

SIZE	DRAWING NO.	REV
B	31-6982	A
	ITEM NO. 31-6982	
	PART NO. 31-6982	