

REVISIONS REV ZONE ECO# DESCRIPTION DRAW APPD DATE INITIAL RELEASE RB CH 8/5/22

VIEW SHOWING WIRE AFTER CRIMPING



RECOMMENDED CRIMP SPECS:					
AWG	ССН	CCW	ICH	ICW	
14	.063061	.102	.132 <u>+</u> .004	.147	
16	.054052	.101	.123 ± .004	.146	
18	.049047	.101	.118 ± .004	.146	




NOTES:

- 1. CRIMP POT WILL ACCOMMODATE SIZE 18AWG THRU 14AWG STRANDED OR SOLID WIRE
- 2. ONLY SURE SEAL APPROVED CRIMPING TOOLS SHALL BE USED TO CRIMP THESE CONTACTS.
- 3. CONTACTS CAN BE ORDERED IN LOOSE PCS. OR IN 5000 PCS. REEL (P/N 110238-0195).
- 4. APPLICABLE ASSEMBLY TOOLS

INSERTION TOOL: CBIT-SS-150 HAND CRIMPING TOOL: SSI-CS10

SEMI-AUTOMATIC CRIMP TOOL (FOR REELS): SSMA-SSI



CONTACT, PIN-STAM	PED (CUSTOMER USE)	\ \ \ \
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MM TOLERANCE EXCEPT AS NOTED: ANGULAR ± 0° 30' DECIMAL .XXX ± .005 DECIMAL .XX ± .01 DECIMAL .XXXX ± .0002	030-2196-001 C O N N E C T I O 2180 Hornig Road, Philadelphia, PA 1:	N S
THIRD ANGLE PROJECTION 💮 亡	RB OH OH 08/05/2022 A NOTICE OF CONFIDENTIALITY THIS DRAWING IS THE PROPERTY OF PER-SORGES, ALL RIG	
STEE A SCALE NTS SHEET 1 OF 1	COPYRIGHT 2018 PEI-GENESIS PARTIES IS STRICTLY PROBLET WITHOUT THE WRITTEN PERM OF ALL MEMORIAL PROPERTY. OF ALL MEMOR	

NOTE: CAD GENERATED DRAWING DO NOT UPDATE MANUALLY.

2A589