









	ARB102-BT			REF: DRB102-BT							1	1.7
QUANTITY	PART NUMBER			DESCRIPTION						ITEM] 🗕	
	•	ı	MAT	ERI	ALS	} LI	ST					\vdash
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows:		SIGNATURES		DATE	Amphenol							
		DRAWN:	HARRIS	14/MAY/24	Amphenoi							
1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08	Fractions ±1/84 Angles ±1°	CHECKED:	ORION	15/MAY/24	Sine Systems - www.amphenol-sine.com					om		
3) Note reference	- <u>x</u>	ENGINEER:			44724 Morley Drive Clinton Township, MI 48036							
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	16/MAY/24								ł
WEIGHT:91.9a		CUSTOMER:			102&1	28 PO	S,BOOT,STRAIGHT,A	RB SI	ERIES	S,BL	ACK	
			S IS SUPPLIED F									
PROCESS SPECIFICATIONS:		SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.		В	C-	ARB102	·BT		1	41		
NEXT ASSY:				SCALE: N	ONE		SHEET	4	OF	5		

Ø31.0±1.0

NOTES: UNLESS OTHERWISE SPECIFIED

- 1. THIS PART IS USED ON ARB12-102P*R-XXXX & ARB12-128P*R-XXXX RECEPTACLE AND ARB16-102S*R-XXXX & ARB16-128S*R-XXXX PLUG (*=A,B,C,D KEYS; XXXX= ALL MODIFICATION)
- 2. TEMPERATURE RATING: -29°C TO +100°C [-20°F TO +212°F]
- 3. BOTTOM OF PART MOLDED OPEN.
- ALL AROUND. ALL THICKNESS ON THIS END MAY VARY.
- 5. SMALL NON-FILLS ARE ACCEPTABLE INSIDE OF PART.
- 6. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.