Mar.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE

Notes 1 Rotation example of Ref. No. ① and ⑥ are shown.
2 The tighteninig torque of Ref. No. ⑥ : 2 to 3 N・m.
3 The tighteninig torque of Ref. No. ⑪ : 0.2 to 0.3 N・m.
Across flats hexagon head of Ref. No. ⑪ : 1.27
Apply Loctite 243 HENKEL JAPAN or equivalent to the threaded portion of Ref. No. ⑪ in order to prevent loosening.



NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
6	Zinc alloy	Nickel plating			
5	Brass	Nickel plating	11	Steel	Nickel plating Hexagon socket set screws M2.6×0.45×2
4	Polyphenylene sulfide	(Black)	10	Brass	Nickel plating Slotted head screw M2×0.4×10
3	Polyphenylene sulfide	(Black)	9	Phosphor bronze	Nickel plating
2	Brass	Silver plating 2μm min.	8	Stainless steel	
1	Zinc alloy	Nickel plating	7	Zinc alloy	Nickel plating

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△1	1	DIS-C-00016502	TY. SUZUKI	HY. KOBAYASHI	20231110

HIROSE ELECTRIC CO., LTD.

APPROVED	HY. KOBAYASHI	20230601	DRAWING NO. EDC-040366-81-00
CHECKED	HY. KOBAYASHI	20230601	PART NO. RM15QPS-2PA(81)
DESIGNED	HT. ZENBA	20230601	
DRAWN	KR. SUZUKI	20230601	CODE NO. CL0109-0896-1-81 △1 1/1