





Note ① The tightening torque of Ref. No. ⑤ : 3 to 4 N·m.  
Apply Loctite 243 HENKEL JAPAN or equivalent to the threaded portion (M17×0.75) of Ref. No. ① in order to prevent loosening.

3	Polyphenylene sulfide	(Black)	6	Phosphor bronze	Nickel plating					
2	Copper alloy	Silver plating 2μm min.	5	Brass	Nickel plating					
1	Brass	Nickel plating	4	Polyphenylene sulfide	(Black)					
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS				
UNITS mm				SCALE 2 : 1		COUNT 1	DESCRIPTION OF REVISIONS DIS-C-00015638	DESIGNED HT. ZENBA	CHECKED HY. KOBAYASHI	DATE 20230621
 HIROSE ELECTRIC CO., LTD.				APPROVED : TP. KOMATSU		20230508	DRAWING NO. EDC-028096-81-00			
				CHECKED : HY. KOBAYASHI		20230508	PART NO. RM15QRD-10PH(81)			
				DESIGNED : HT. ZENBA		20230508	CODE NO. CL0109-0855-4-81			
				DRAWN : KR. SUZUKI		20230508	 1			