

Part No.	Cable color
~084N~	WHITE
~084N1~	---
~084H~	BLACK
~084N2~	---

NOTE 1 We indicate the length of the harness on the last of product name, 'L' part.


2 Tolerance for [L]

Length L [mm]	Tolerance [mm]
$35 \leq L \leq 200$	± 4
$200 < L \leq 500$	± 8
$500 < L \leq 1000$	± 12
$1000 < L$	$\pm 1.5\%$

3 Connector rotation angle is within ± 45 degree from the above image.
For long length in the case of $L > 500$, the angle is optional.

4. Specifications are subject to change without notice.


[DIMENSIONS OF CONNECTOR]



1 For stable supply of this series, material supplier of piece part#1 will be changed during 2019-2022. Please note this change in advance. There will be no difference in product performance and quality.

[PRECAUTIONS FOR HANDLING]

- ◆ Connector insertion and extraction
 - a. Connector shall be extracted vertically by specialised extraction JIG.
Part No.: H.FL-LP-NCCL Code: CL331-0551-7>
Never hold the cable when extracting the cable because it damages the connector.
 - b. Insert the connector as perpendicularly to the mating surface as possible by aligning the mating axes of both connectors. Do not excessively slant the connectors when inserting.



2	H.FL75-CONTACT	CL331-0550-4-00		
1	H.FL75-LP-084(C01)	CL331-0541-3-01	3	1.5Dia. coaxial cable
NO.	PART NO.	CODE NO.	NO.	PART NO.
UNITS mm		SCALE FREE	COUNT 1	DESCRIPTION OF REVISIONS DIS-D-00003994
APPROVED : NK. NINOMIYA 20180611		DRAWING NO. EDC-383474-00-00		
CHECKED : MT. KANEKO 20180611		PART NO. H.FL75-2LP-084*-A-L 1		
DESIGNED : MS. MATSUMOTO 20180611		CODE NO. CL321-5111-4-00 1/1		
DRAWN : MS. MATSUMOTO 20180611				