NOTES:

1. MATERIALS AND FINISHES:
   REAR BODY AND BAYONET SLEEVE - BRASS, NICKEL PLATING
   OUTER CONTACT - BeCu, NICKEL PLATING
   CONTACT - PHOSPHOR BRONZE, GOLD PLATING
   FERRULE - COPPER, NICKEL PLATING
   INSULATOR - PTFE, NATURAL
   INSULATOR-REAR - PTFE, NATURAL
   CAP - STAINLESS STEEL, PASSIVATED

2. ELECTRICAL:
   A. IMPEDANCE: 75 OHM
   B. FREQUENCY RANGE : DC - 18 GHz
   C. RETURN LOSS:-20dB DC-6 GHz
   -15dB 6-12 GHz

3. MECHANICAL:
   A. DURABILITY: 500 CYCLES MIN.
   B. TEMPERATURE : -65 C TO +165 C

4. ENVIRONMENTAL:
   A. THERMAL SHOCK PER MIL-STD-202 METHOD 107
   TEST CONDITION B (EXCEPT HIGH TEMP @200°C)
   B. VIBRATION: MIL-STD-202 METHOD 204 TEST CONDITION B
   C. SHOCK: MIL-STD-202 METHOD 213 TEST CONDITION B
   D. CORROSION: MIL-STD-202 METHOD 101
   TEST CONDITION B 5% SALT SOLUTION

5. PACKAGING:
   A. QUANTITY: SINGLE PACK
   B. MARKING: BAG TO BE MARKED:
   "AMPHENOL RF, 34-1118-12G DATE CODE"

6. HIGH DENSITY INSTALLATION/REMOVAL TOOL: 227-T2000

7. CABLE ASSEMBLY INSTRUCTIONS:
   A. TRIM CABLE AS SHOWN.
   B. SLIDE FERRULE ONTO CABLE.
   C. INSERT INSULATOR-REAR ONTO CENTER CONDUCTOR IN ORIENTATION SHOWN.
   D. INSERT CABLE WITH INSULATOR-REAR INTO CONNECTOR WITH FOIL ENTERING
   CONNECTOR AND BRAID OVER KNURL
   E. SOLDER CONTACT TO CABLE CENTER CONDUCTOR.
   F. CRIMP FERRULE WITH .213" HEX.

8. CAP ASSEMBLY INSTRUCTIONS:
   A. ASSEMBLE CAP TO BODY WITH 5 IN-LBS MAX TORQUE.

9 SHOWS CABLE ENTRY DIMENSIONS.

REVISIONS				
REV	DESCRIPTION	DATE	ECN	BY
A	RELEASE TO MFG.	26-MAR-18	07342	KCE
B	BODY AND REAR BODY WERE CHANGED	27-NOV-18	09746	SC
C	OUTER CONTACT,REAR BODY AND INSULATOR-REAR WERE CHANGED	05-AUG-24	17144	SCOTT





SCALE 2.000



RECOMMENDED CABLE STRIPPING DIMENSIONS

CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

THIRD ANGLE PROJ.

REFERENCE	EAR#
	8067

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE METRIC [INCHES] AND TOLERANCES ARE:

<0.5mm = ±0.05mm	[<0.020 = ±0.002]
0.5 - 6mm = ±0.1mm	[0.020 - 0.236 = ±0.004]
>6.00 - 30mm = ±0.2mm	[>0.236 - 1.181 = ±0.008]
>30.00 - 120mm = ±0.3mm	[>1.181 - 4.725 = ±0.012]

ANGLES = ±1°

MATERIAL

ENGR.1	ENGR.2	DATE
STAR	BRANDON	27-NOV-18

TITLE: 75 OHM HD BNC RA PLUG FOR BELDEN 4855R

SHEET NO. 2 OF 2 | SCALE: 5.0:1.0

Amphenol RF

SIZE	DRAWING NO.	REV
B	34-1118-12G	C
	ITEM NO. 34-1118-12G	
	PART NO. 34-1118-12G	