
•	PART NO.		REVISIONS								
💿 multicomp	I		ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
			-	Α	RELEASED	Veena	31/7/08	Suresh	31/7/08	G. C	15/8/08
4P	Specifications: Current rating Voltage rating Maximum contact resistance Minimum insulation resistance Withstanding voltage Operating temperature range Materials and Finish: Insulator Contact Plating Mating with Application wire	ent rating: 5.0A acage rating: 250V acimum contact resistance: 10m $\Omega$ .mum insulation resistance: 1000Mistanding voltage: 1500V acrating temperature range: -40°C toerials and Finish::lator: High tentact: Phosphng: Tin platng with: 5561T to		°C. ure pla nze. Il.							

## **Specification Table**

Number of Positions	ber of Positions A		Part Number		
4	3.00	6.85	2261(5561)-04		
			D' I MIT I		

Dimensions : Millimetres

## Part Number Explanation:



## **Number of Positions** : 04 = 4 Positions.

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the prod- ucts for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or or	TOLERANCES:	DRAWN BY:	DATE:	DRAWING TITLE:				
	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	Veena	31/07/08	Plug - Panel Mount, 4 Way				
		CHECKED BY:	DATE:	SIZE DWG NO.		ELECTRONIC FILE	REV A	
		Suresh	31/07/08	Δ	M10001325	578573-1578582_2_DWG		
		APPROVED BY:	DATE:					
		G.Cook	15/08/08	SCALE: NTS	U.O.M.: mm	SHEET: 1 O	F 1	