
	PART NO.		REVISIONS							
	2260(5560)-04	ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
		-	А	RELEASED	Ramya	04/8/08	Suresh	04/8/08	G. C	18/8/08

_ _ .




Specifications:

Current rating	: 5.0A ac/dc.
Voltage rating	: 250V ac/dc.
Maximum contact resistance	: 10mΩ.
Minimum insulation resistance	: 1000MΩ.
Withstanding voltage	: 1500V ac/minute.
Operating temperature range	: -25°C to +105°C.
Material and Finish:	
Insulator	: High temperature
Contact	: Phosphor bronze.
Plated	: Tin plated.
Mating with	: 5560T terminal.

105°C.

- erature plastic (nylon 66).
- oronze.
- inal.



Dimensions : Millimetres


This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for	TOLERANCES:	DRAWN BY:	DATE:	DRAWING TITLE:				
information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change with- out notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or ornission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the prod- ucts for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	Ramya	04/08/08	Receptacle - Free, 4 Way				
		CHECKED BY:	DATE:	SIZE DWG NO.	M10001553	ELECTRONIC FILE	REV	
		Suresh	04/08/08	Δ		1578562-1578572_2_DWG	A	
		APPROVED BY:	DATE:				<u> </u>	
		G.Cook	18/08/08	SCALE: NTS	U.O.M.: mm	SHEET: 1 OF	F 2	

	PART NO.		REVISIONS							
	2260(5560)-04	ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
		-	А	RELEASED	Ramya	04/8/08	Suresh	04/8/08	G. C	18/8/08

Specification Table

Number of Positions	А	В	Part Number
4	3.00	6.85	2260(5560)-04
		•	Dimensions : Millimetres

Part Number Explanation:



Number of Positions : 04 = 4 Positions.

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for	TOLERANCES:	DRAWN BY:	DATE:	DRAWING TITLE:				
information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change with- out notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information abased on information included or ucts for their purpose and not make any assumptions based on information or omitted. Liability for loss or damage resulting from any reliance on the Information or	UNLESS OTHERWISE	Ramya	04/08/08	Receptacle - Free, 4 Way				
	SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	CHECKED BY:	DATE:	SIZE DWG NO.		ELECTRONIC FILE	REV	
		Suresh	04/08/08	Α	M10001553	1578562-1578572_2_DWG	A	
		APPROVED BY:	DATE:					
		G.Cook	18/08/08	SCALE: NTS	U.O.M.: mm	SHEET: 2 OF	F 2	