

CP SNT 24W 24V 1A

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-2083
 www.weidmueller.com



One-phase switched-mode power unit in installation housing in performance classes 24 and 48 W. .
 The INSTA power units can be universally deployed because of their wide input range from 85 V AC to 265 V AC.
 They are available with output voltages from 5 V to 48 V.

General ordering data

Order No.	9928890024
Part designation	CP SNT 24W 24V 1A
Version	Power supply, switch-mode power supply unit, 24 V
GTIN (EAN)	4032248217557
Qty.	1 pc(s).

CP SNT 24W 24V 1A

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-2083
 www.weidmueller.com

Technical data

Dimensions

Length	62.5 mm	Width	52 mm
Height	90.5 mm		

Temperature

Ambient temperature (operational)		Ambient temperature (operational)	-20 °C...+50 °C
Storage temperature	-40 °C...+85 °C		

Input

Conductor connection system	Screw connection	DC input voltage range	120...300 V DC
Input current	460 mA @ 115 V AC; 250 mA @ 230 V AC	Input current at 115 Vac	460 mA RMS ± 20%
Input current at 125 Vdc	235 mA ± 20%	Input current at 250 Vdc	120 mA ± 20%
Input frequency	50/ 60 Hz	Input fuse	2 A time-lag fuse (internal)
Input voltage (voltage mode input)	85...265 V AC, 120...300 V DC	Input voltage range AC	85...265 V AC
Surge protection	Varistor	making current limit	Thermistor

output

Conductor connection system	Screw connection	Control at 10...100% load	0.5 %
Control at input voltage	0.2 %	Mains failure bridge-over time	35 ms @ 115 V AC / 160 ms @ 230 V AC
Mains failure bridge-over time for 115 V AC	35 ms	Mains failure bridge-over time for 230 V AC	160 ms
Max. capacitance at output	8000 µF	Max. residual ripple	< 2 %
Output current	1 A	Output power, max.	24 W
Output voltage	24 V DC	Overload protection	Surge current / thermal cut-out
Surge protection	Varistor	rated output voltage	24 V DC ± 1 %

General data

Ambient temperature (operational)		DIN Rail compatibility	TS 35
Degree of efficiency at max. load	78 %	EMC standards	EN 61000-6 /-2, -3
Mounting position, installation notice	horizontally on terminal rail TS 35	Standards	EN 50178 EN 60950 IEC950
Ambient temperature (operational)	-20 °C...+50 °C		

Insulation coordination

electrical isolation, I/O rail	4 kV	electrical isolation, input-earth	1.5 kV
electrical isolation, input-output	3 kV	electrical isolation, output-earth	0.5 kV

Approvals

Approvals institutes	CSA; CSAEX; GOSTME25; CE
----------------------	--------------------------

Classifications

ETIM 4.0	eClass 6.0	EC27049201
----------	------------	------------

CP SNT 24W 24V 1A**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-2083

www.weidmueller.com**Technical data****Notes**

Note, technical data

Derating loss: 33% @ 60°C The internal varistor found in a switch-mode power supply does not replace the need for surge protection within a system.

Datasheet

CP SNT 24V 24V 1A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com

Drawings

Electric symbol

