

- ◆ Rugged metal case for harsh industrial environments
- ◆ Industrial operating temperature range: -25°C to +70°C
- ◆ Overload and and overtemperature protection
- ◆ Power boost up to 120 %
- ◆ Power-Good signal
- ◆ Shock and vibration proof
- ◆ International safety approval package
- ◆ ATEX certification for hazardous locations
- ◆ Wall mounting (opt.)
- ◆ 3-year product warranty



The TSPC series are high performance DIN-rail mount power supplies for harsh industrial environments. The design is based on the popular TRACOPOWER TSP series but with reduced electrical features to make these power supplies an easy to install and cost efficient but reliable solution for basic applications. Excellent electrical specifications and high immunity against electrical disturbances makes these compact modules the best choice for reliable industrial systems and machines.

For system applications all models provide a Power-Good signal.

The TSPC series power supplies complies with the latest safety and EMC standards for industrial environments and include ATEX EN 60079 certification and IEC 60079 test report for applications in hazardous locations.

Models

| Order Code | Output Power nominal | Output Voltage nominal | Output Current nominal |
|-------------|-------------------------|---------------------------|---------------------------|
| TSP 080-124 | 80 W | 24 VDC | 3.3 A |
| TSP 120-124 | 120 W | | 5.0 A |
| TSP 240-124 | 240 W | | 10 A |
| TSP 480-124 | 480 W | | 20 A |

Input Specifications

| | | |
|---|---|--|
| Input voltage | – nominal ranges – effective ranges – output power derating at input <100 VAC | 100 – 120 / 220 – 240 VAC by selection switch 85 – 132 / 187 – 264 VAC 3.3 %/V |
| Input voltage frequency | | 47 – 63 Hz |
| Harmonic limits | | EN 61000-3-2 |
| Holdup time | | 10 ms min. |
| Inrush current | | 40 A |
| Recommended circuit breaker, characteristic C or fuse, slow blow type | – TSP 080/120 – TSP 240 – TSP 480 | 6.0 – 16.0 A 10.0 – 16.0 A 16.0 – 25.0 A |
| Efficiency | | 85 – 92 % |


Output Specifications

| | | |
|------------------------------------|---|--|
| Output voltage adj. range | – output power derating above 24 VDC | 24 – 28 VDC 5 %/V |
| Boos output current | – power derating above 50°C ambient – power derating at input <115 VAC – power derating at input <220 VAC | 120 % (at 24 VDC output voltage) continuous at <50°C ambient temperature 2 %/°C 1.3 %/V 0.6 %/V (at upper input voltage range) |
| Regulation | – Input variation – Load variation (0–100 %) | 1 % max. 1 % max. |
| Ripple and Noise (20MHz bandwidth) | | 100 mVp-p typ. (200 mVp-p max.) |
| Overload protection | | 120 – 140 % of Iout nom., constant current |
| Short circuit current | | 90 % of Iout nom. (typ.), foldback |
| Output overvoltage protection | | 45 V |
| Overtemperature protection | | switch off at overtemperature, automatic restart |
| Power back immunity | | 35 V (40 V for 1 sec.) |
| Power OK signal | – trigger threshold: – output signal | 21.0 – 22.5 V open collector 10 mA max. |
| Max. capacitive load | | unlimited |

General Specifications





| | | |
|--|---|-------------------------------------|
| Temperature range | – Operating – output current derating above 60°C ambient | –25°C to +70°C max. 2.5 %/°C |
| Cooling | | convection cooling, no internal fan |
| Humidity (non condensing) | | 95 % rel. H max. |
| Pollution degree | | 2 |
| Temperature coefficient | | 0.02 %/K |
| Reliability, calculated MTTF (@ +25°C acc. to IEC 61709) | | tba. |

General Specifications

| | | |
|--|--|---|
| Isolation | | according to IEC/EN 60950-1, UL 60950-1, UL 508 |
| Safety standards | <ul style="list-style-type: none"> – Information technology equipment – Industrial control equipment – Electrical equipment for machines – Electronic equipment for power installation – Safety transformers for SMPS – Control equipment for hazardous location | IEC/EN 60950-1, UL 60950-1, CSA 22.2 No 60950-1-07 UL 508, CSA-C22.2 No. 107 EN 60204-1 EN 50178 EN 61558-2-4 IEC/EN 60079-15  II3G EX nA IIC T4 |
| Safety approvals and certifications | <ul style="list-style-type: none"> – CB report – UL approvals – ATEX (for IP 54 enclosure) – IECEx certificate – Certificate for other standards (Bureau Veritas) | IEC/EN 60950-1 www.tracopower.com/products/tspc-cb.pdf UL 60950-1, CSA 22.2 No. 60950-1-07 www.tracopower.com/products/tspc-ul60950.pdf UL 508C listed File: E210002 (entry pending) www.ul.com -> certifications certificate no. EPS 10 ATEX 1 269 X www.tracopower.com/products/tspc-atex.pdf IEC 60079-0, IEC 60079-15 www.tracopower.com/products/tspc-iecex.pdf EN 60950-1, EN 60204-1, EN 61558-2-4 www.tracopower.com/products/tspc-bv.pdf |
| Class of protection | | safety class I (IEC 536) |
| Degree of protection | | IP 20 (IEC/EN 60529) |
| Electromagnetic compatibility (EMC), Emissions | <ul style="list-style-type: none"> – Conducted RI suppression on input – Radiated RI suppression | EN 61000-6-3, EN 61204-3 EN 55011 class B, EN 55022 class B, EN 55011 class B, EN 55022 class B, |
| Electromagnetic compatibility (EMC), Immunity | <ul style="list-style-type: none"> – Electrostatic discharge (ESD) – Radiated RF field immunity – Electrical fast transient / burst immunity – Surge immunity – Immunity to conducted RF disturbances – Power frequency field immunity – Mains voltage dips and interruptions | EN 61000-6-2, EN 61204-3 IEC/EN 61000-4-2 4 kV / 8 kV criteria B IEC/EN 61000-4-3 10 V / m criteria A IEC/EN 61000-4-4 2 kV criteria B IEC/EN 61000-4-5 1 kV / 2 kV criteria B IEC/EN 61000-4-6 10 V criteria A IEC/EN 61000-4-8 30 A / m criteria A IEC/EN 61000-4-11 criteria B/C |
| Environment | <ul style="list-style-type: none"> – Vibration acc. IEC 68-2-6; – Shock acc. IEC 60068-2-27 | 3 axis, sine sweep, 10 – 55 Hz, 1 g, 1 oct/min 3 axis, 15 g half sine, 11 ms |
| Enclosure material | | aluminium (chassis) / stainless steel (cover) |
| Mounting | <ul style="list-style-type: none"> – DIN-rail mounting – Wall mounting (option) | for DIN-rails as per EN 50022-35x15/7.5 (snap-on with self-locking spring) with wall mounting bracket - see page 12 |
| Connection | <ul style="list-style-type: none"> – Input / Output – Power Good signal | screw terminals connector tba. |
| Installation instructions | | www.tracopower.com/products/tspc-inst.pdf |

Outline Dimensions

TSPC 080-124







Weight: 2.8kg (6.0lb)

Dimensions in [mm], () = Inch
Tolerances: ± 0.5 mm (± 0.02)

Outline Dimensions

TSPC 120-124







Weight: 2.8kg (6.0lb)

Dimensions in [mm], () = Inch
Tolerances: ±0.5 mm (±0.02)

Outline Dimensions

TSPC 240-124





Weight: 2.8kg (6.0lb)

Dimensions in [mm], () = Inch
Tolerances: ± 0.5 mm (± 0.02)

Outline Dimensions

TSPC 480-124




Weight: 2.8kg (6.0lb)

Dimensions in [mm], () = Inch
Tolerances: ±0.5 mm (±0.02)

TSP-WMK Wall Mounting Bracket


| order code | for models | content of kit |
|------------|------------------------------|----------------|
| TSP-WMK03 | TSPC 080, TSPC 120, TSPC 240 | 1 bracket |
| TSP-WMK02 | TSPC 480 | 2 brackets |

TSP-WMK03



Material: 2 mm Mild Steel
Tolerance: ±0.1mm (±0.004)

TSP-WMK02



Material: 2 mm Mild Steel
Tolerance: ±0.1mm (±0.004)

Dimensions: [mm] () = Inch

Dimensions in [mm], () = Inch
Tolerances: ±0.5 mm (±0.02)

Specifications can be changed any time without notice.