Productname :BELT DRESSING FGCreationdate :23.11.10Ref.Nr.:UK10580-3-231110Replaces:12.01.09

1. IDENTIFICATION OF PRODUCT AND COMPANY

Productname: BELT DRESSING FG

Aerosol

Application: Lubricants

Company: CRC Industries UK Ltd.

Castlefield Industial Estate, Wylds Rd, Bridgwater,

Somerset, UK, TA64DD

Tel.: (+44)(0)1278 727200 Fax: (+44)(0)1278 425644 E-mail: hse.uk@crcind.com

In case of emergency: (+44)(0)1278 727200

Subsidiaries		Tel	Fax
CRC Industries Europe	Touwslagerstraat 1 9240 Zele Belgium	(+32) (0) 52 / 45 60 11	(+32) (0) 52 / 45 00 34
CRC Industries Finland	Asemanrinne 13, 08500 Lohja AS	(+358)(0)19/32921	(+358)(0)19/383676
CRC Industries France	12, Bld des Martyrs de Chateaubriant F-95102 Argenteuil Cédex	(+33)(0)1/34112000	(+33)(0)1/34110996
CRC Industries Deutschland	Südring 9, 76473 Iffezheim	(+49)(0)7229/3030	(+49)(0)7229/303266
CRC Industries Iberia	Gremio del cuero S/N, 40195 Segovia	(+34)921/427546	(+34)921/436270
CRC Industries Sweden	Kryptongatan 14, 43153 Mölndal	(+46)(0)31/7068480	(+46)(0)31/273991

2. HAZARD IDENTIFICATION

Health and Safety: Extremely Flammable

(propane/butane propellant)

Irritating to skin.

Vapours may cause drowsiness and dizziness.

Remark: Preparations classified as harmful on the basis of an aspiration hazard need not be labelled as harmful

with R65 when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment. (EU-Directive 67/548 Annex VI 9.4)

Environment : Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.



BELT DRESSING FG Productname: Creationdate: 23.11.10 Ref.Nr.: UK10580-3-231110 12.01.09 **Replaces:**

Other hazards: Pressurised container: protect from sunlight and do not

expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame

or any incandescent material.

Without adequate ventilation formation of explosive

mixtures may be possible.

3. COMPOSITION AND INFORMATION ON COMPONENTS

Hazardous ingredient	CAS-nbr.	EINECS	w/w %	symbol	R-phrases*	Notes
Naphtha (petroleum), hydrotreated light (benzene<0.1%)	64742-49-0	265-151-9	30-60	F,Xn,N	11-38-51/53-65-67	В,Р
Hydrocarbons, C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	68512-91-4	270-990-9	30-60	F+	12	K
Explanation notes						
B: substance with national established workplace exposure limit						
K: not classified as carcinogen, less than						
0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)						
P: not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7)						

^{(*} Explanation risk-phrases : see chapter 16)

4. FIRST AID MEASURES

General Advice: The usual precautions for handling chemicals should be

observed

If any symptoms should occur, seek medical advice.

Contact with eyes: If substance has got into eyes, immediately wash out

with plenty of water

Contact with skin: Remove contaminated clothing immediately and drench

affected skin with plenty of water. Then wash with

soap and water

Seek medical advice

Inhalation: Fresh air, keep warm and at rest.

Seek medical attention if ill effects occur

Ingestion: Ingestion is unlikely to occur

> If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected

obtain immediate medical attention

5. FIRE-FIGHTING MEASURES

Flash point (without propellant): < 0 °C



Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6 4DD

Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.crcind.com

Productname : BELT DRESSING FG **Creationdate :** 23.11.10 **Ref.Nr.:** UK10580-3-231110 **Replaces:** 12.01.09

Explosion limits : upper limit : Not available.

Not available.

Extinguishing media: foam, carbon dioxide or dry agent

Fire-fighting procedures: Keep container(s) exposed to fire cool, by spraying

with water

Unusual exposure hazard : Aerosols may explode if heated above 50°C

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Shut off all ignition sources

Ensure adequate ventilation

Wear suitable protective clothing and gloves.

Environmental precautions: Do not allow to enter public sewers and watercourses

If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

Cleaning methods: Absorb spillage in suitable inert material

7. HANDLING AND STORAGE

Handling procedures: Use only in well ventilated areas

Keep away from heat and sources of ignition Do not spray on a naked flame or incandescent

material.

Do not pierce or burn aerosols, even after use.

Do not breathe aerosols or vapours. Avoid contact with skin and eyes.

Storage procedures: Pressurized container: protect from sunlight and do not

expose to temperatures exceeding 50°C. Keep in a cool, dry, well ventilated place

Keep out of reach of children.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Control procedures : Ensure adequate ventilation

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Personal protection: Use only in well ventilated areas

It is advisable to take precautions to avoid contact with

skin and eyes when handling the product.

inhalation: In case of insufficient ventilation, wear suitable

respiratory equipment. (Filter type AX)

hands and skin: Wear suitable protective gloves

(nitrile)

eyes: Wear safety goggles.



Ambersil House, Wylds Road, Castlefield Industrial Estate,

Bridgwater, Somerset, TA6 4DD

Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.crcind.com

Productname : BELT DRESSING FG **Creationdate :** 23.11.10 **Ref.Nr.:** UK10580-3-231110 **Replaces:** 12.01.09

9. PHYSICAL AND CHEMICAL PROPERTIES (for aerosols without propellant)

Apperance : physical state : Propane/butane propelled liquid.

colour: Colorless.

odour: Characteristic odor.

Boiling point/range : Not available.

Relative density : $0.794 \text{ g/cm} 3 \text{ (@ } 20^{\circ}\text{C)}.$

pH: Not applicable.
Vapour pressure: Not available.
Relative vapour density: Not available.
Solubility in water: Insoluble in water

Flash point : $$<0\,^\circ C$$ Auto-ignition : $$>200\,^\circ C$$ Viscosity : Not available.
Evaporation rate : Not applicable.

10. STABILITY AND REACTIVITY

Conditions to be avoided: Pressurized container: protect from sunlight and do not

expose to temperatures exceeding 50°C. Keep away from heat and sources of ignition

Materials to be avoided: Strong oxidising agent

Hazardous decomposition compounds : CO,CO2

11. TOXICOLOGICAL INFORMATION

Inhalation: Excessive inhalation of solvent vapours may give rise

to nausea, headaches and dizziness

Ingestion: Ingestion is unlikely to occur

After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical

pneumonia.

Skin contact: Irritating to skin

12. ECOLOGICAL INFORMATION

Other adverse effects: Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Do not allow to enter public sewers and watercourses



Productname : BELT DRESSING FG **Creationdate :** 23.11.10 **Ref.Nr.:** UK10580-3-231110 **Replaces:** 12.01.09

13. WASTE DISPOSAL

Product: Do not discharge into drains or the environment,

dispose to an authorised waste collection point.

This material and its container must be disposed of in a

safe way.

Disposal should be in accordance with local, state or

national legislation

14. TRANSPORT

UN-number: 1950

Road/Rail - ADR/RID: UN1950 Aerosols Class: 2, PG: NA, Class code: 5F,

Label: 2.1, Tunnel-code: (D)

Environmentally hazardous YES

Sea - IMDG: UN1950 Aerosols Class: 2, PG: NA, Label: 2.1

EmS F-D,S-U

Marine pollutant P

Air - IATA/ICAO : UN1950 Aerosols, flammable Class : 2, PG : NA,

Label: 2.1

Environmentally hazardous YES

15. REGULATORY INFORMATION

Warning symbol(s): F_+ : EXTREMELY FLAMMABLE

Xi: IRRITANT

N: DANGEROUS FOR THE ENVIRONMENT

Risk-phrase(s): R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause longterm adverse effects in the aquatic environment. R67: Vapours may cause drowsiness and dizziness.

Safety-phrase(s): S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No

smoking.

S23: Do not breathe vapours/spray.

S35: This material and its container must be disposed

of in a safe way.

S51: Use only in well-ventilated areas.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Without adequate ventilation formation of explosive mixtures may be possible.



Material Safety Data Sheet Regulation EC No 1907/2006 Art.31 Productname: BELT DRESSING FG Creationdate: 23.11.10 Ref.Nr.: UK10580-3-231110 Replaces: 12.01.09

Classified according to Dir. 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC. Classification according to EU-directive 99/45/EC

Remark: Preparations classified as harmful on the basis of an aspiration hazard need not be labelled as harmful with R65 when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment. (EU-Directive 67/548 Annex VI 9.4)

16. OTHER INFORMATION

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

REVISIONS IN CHAPTRE: 14

*Explanation risk-phrases: R11: Highly flammable.

R12: Extremely flammable.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.
R67: Vapours may cause drowsiness and dizziness.

This Material Safety Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Material Safety Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com. We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

