





Multicomp Packaging Label

Per ANSI/ESD S541 section 7.2.2 Resistance of Dissipative Materials "A static dissipative material shall have a surface resistance of greater than or equal to 1.0 x 10E4 Ohms but less than 1.0 x 10E11 Ohms. Packaging materials that are in intimate contact with devices should be dissipative."

## **Features**

- Economical method of storing ESD senstive items in ESD protected areas
- Shipped knocked-down; easy to assemble
- Identified as static control product marked with ESD protective symbol per ANSI/ESD S8.1
- Made in America

## **Specifications:**

- Manufactured from Protektive Pak impregnated corrugated material meeting ANSI/ESD S20.20 and Packaging standard ANSI/ESD S541
- Dissipative surface Rtt 10E6 to less than 10E9 ohms tested per ANSI/ESD STM11.11
- Per ANSI/ESD S541 dissipative material can be grounded and "provides an electrical path for charge to dissipate from the package".

Item #	Size OD (L x W x D)
MC36089	24 3/4 x 4 1/4 x 4 1/2
MC36090	24 3/4 x 2 1/4 x 4 1/2
MC36091	18 x 4 x 4 1/2
MC36092	18 x 2 x 4 1/2
MC36093	12 x 4 x 4 1/2
MC36094	12 x 2 x 4 1/2



"Specifications and procedures subject to change without notice."

## **OPEN BIN BOXES**



DRAWING NUMBER
MC36089

**DATE**January
2011