

EVERBUILD FLOOR PAINT

DESCRIPTION

EVERBUILD FLOOR PAINT is a low viscosity, high solids, heavy duty polyurethane based floor paint designed to provide a clean hard wearing finish to concrete, stone and wooden floors subject to light traffic including fork lift trucks, scissor lifts etc. ideal for use on garage floors, workshops, storerooms, walkways etc. EVERBUILD FLOOR PAINT gives enhanced durability, abrasion resistance and a good resistance to dilute acids/alkalis and oils.

BENEFITS

- Hard wearing polyurethane formula
- Low viscosity for easy application over large areas
- Can be applied to new/old concrete

AREAS FOR USE

Concrete, stone and wooden floors in garages, workshops, storerooms, and cloakrooms etc.

LIMITATIONS

Ready to use product. Do not dilute. Always follow manufacturers instructions carefully.

New concrete must be a minimum of 6 months old before painting.

Suitable for light traffic only, for areas subject to heavy traffic or constant use, an epoxy-based product is recommended.

Do not use on bitumen or asphalt.

Mechanically or chemically hardened floors may need abrasion prior to application.

As the company cannot be aware of all applications and materials the product can be used on, it is the users responsibility to determine suitability for use. If in doubt contact technical services for advice or request technical data sheet.

SURFACE PREPARATION

All surfaces must be clean, dry (to touch) and free grease and other contaminants. Remove all loose and flaking material with a scraper and a stiff brush back to a sound surface. Remove all moss/mould contamination with EVERBUILD MOSS AND MOULD REMOVER. Chemically or mechanically hardened floor may need abrasion prior to use. If in doubt test a small area prior to full application.

APPLICATION

Concrete must be a minimum of 6 months old before paint can be applied. Priming is not normally required however if necessary apply a priming coat of 1 part white spirit to 4 parts paint and allow to dry. EVERBUILD FLOOR PAINT is touch dry in 2-3 hours depending on ambient temperatures. NOTE low temperatures can significantly extend drying time. Apply using a brush or roller to give an even coating. 2 coats are normally required allowing 12 hours between coats. Clean tools and brushes with white spirits/turps subs after use. Cured product can be removed using xylene.

SPECIFIC DATA

Colour	Grey/red
Solids(W/W)	68-75%
Specific Gravity	1.2-1.3 g/cm ³
M. F. F. T	> 0°C
Film Thickness (dry)	0.4 microns
Shelf Life	12 months
Drying time	Touch dry; 2-3 hours, 12 hours between coats.

HEALTH AND SAFETY

Flammable, contains white spirit. Keep away from sources of ignition. Use in well ventilated areas. Do not empty in drains or watercourses. Store only in original container. If product enters eyes rinse for 15 minutes and seek medical advice. If swallowed obtain immediate medical attention, show can or label where possible.

STORAGE

Store in cool, dry conditions, between 5 and 25°C. PROTECT FROM FROST. Shelf life 12 months from date of manufacture.