Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

83028 Hook-up/Lead - UL AWM Style 1180

For more Information please call

1-800-Belden1



Description:

Stranded silver-coated copper conductor insulation with extruded TFE Teflon.

Physical Characto	ristics (Ωy)	orall)				
Physical Characte Conductor		erall)				
AWG:						
# Conductors AWG	-					
1 20	7x28 SP	C - Silver Plated Coppe				
Insulation Insulation Material:						
Insulation Material	Wall Thi	ckness (mm)				
TFE - Tetrafluoroeth		, , ,				
Overall Insulation						
Overall Cabling						
Overall Nominal E	Diameter:		1.727 mm			
Applicable Specifi	cations an	d Agency Com	oliance (Overall)			
Applicable Standar	ds & Enviro	nmental Program	IS			
UL AWM Style:			1180			
UL Rating:			300 V RMS, 200°C			
Other Standards:			MIL-W-16878/5			
EU CE Mark:			Yes			
EU Directive 2000	/53/EC (ELV):	-	Yes			
EU Directive 2002	EU Directive 2002/95/EC (RoHS):					
EU RoHS Compliance Date (mm/dd/yyyy):			04/01/2005			
EU Directive 2002/96/EC (WEEE):			Yes			
EU Directive 2003/11/EC (BFR):			Yes			
CA Prop 65 (CJ for Wire & Cable):			Yes			
MII Order #39 (China RoHS):			Yes			
Military Specification:			1000 V, 200°C			
Flame Test						
UL Flame Test:			VW-1			
Plenum/Non-Plenu	n					
Plenum (Y/N):			No			
Related Document	s:					
No related documents are a		product				
Put Ups and Color	S:					
Item #	Putup	Ship Weight	Color	Notes	Item Desc	
83028 001100	30 MT	0.272 KG	BROWN		#20 STR TFE BRN	

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

83028 Hook-up/Lead - UL AWM Style 1180

83028 0011000	305 MT	3.175 KG	BROWN	SW	#20 STR TFE BRN
83028 002100	30 MT	0.272 KG	RED		#20 STR TFE RED
83028 0021000	305 MT	3.175 KG	RED	SW	#20 STR TFE RED
83028 003100	30 MT	0.272 KG	ORANGE		#20 STR TFE ORG
83028 0031000	305 MT	3.175 KG	ORANGE	SW	#20 STR TFE ORG
83028 004100	30 MT	0.272 KG	YELLOW		#20 STR TFE YEL
83028 0041000	305 MT	3.175 KG	YELLOW	SW	#20 STR TFE YEL
83028 005100	30 MT	0.272 KG	GREEN, DARK		#20 STR TFE GRNDK
83028 0051000	305 MT	3.175 KG	GREEN, DARK	SW	#20 STR TFE GRNDK
83028 006100	30 MT	0.272 KG	BLUE, LIGHT		#20 STR TFE BLULT
83028 0061000	305 MT	3.175 KG	BLUE, LIGHT	SW	#20 STR TFE BLULT
83028 0071000	305 MT	3.175 KG	VIOLET	SW	#20 STR TFE VIO
83028 0081000	305 MT	3.175 KG	GRAY	SW	#20 STR TFE GRY
83028 009100	30 MT	0.272 KG	WHITE		#20 STR TFE WHT
83028 0091000	305 MT	3.175 KG	WHITE	SW	#20 STR TFE WHT
83028 010100	30 MT	0.272 KG	BLACK		#20 STR TFE BLK
83028 0101000	305 MT	3.175 KG	BLACK	SW	#20 STR TFE BLK

Notes:

S = STRIPING ADDERS FOR TYPES E AND EE: 123 STRIPES. MINIMUM ORDER10

W = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 75'

Revision Number: 1 Revision Date: 05-14-2007

© 2011 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the action belief at the date of the product product before the product because a part is because a part of Their Disclosure is not for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.