Detailed Specifications & Technical Data

No longer Available



ENGLISH MEASUREMENT VERSION

9454 Coax - Dual Channel Audio Cable

For more Information please call

1-800-Belden1



Description:

Dual channel, 30 AWG stranded (7x38) TCCS conductors, FPE insulation, individual tinned copper spiral wrapped shield (85% coverage), PVC jacket, polarity ribbed.

Physical Characteristics (Overall)	
Conductor AWG:	
# Coax AWG Stranding Conductor Material	Dia. (in.)
2 30 7x38 TCCS - Tinned Copper Covere	
Insulation	
Insulation Material:	
Insulation Material Wall Thickness (in.) Dia. (in	
FPE - Foam Polyethylene .049 .110 +/-	003
Insulation Color Code Chart:	
Number Color 1 Red	
2 White	
Inner Shield	
Inner Shield Material:	
Type Inner Shield Material Coverage (%) Spiral Same TC Timed Conners 95	
Spiral Serve TC - Tinned Copper 85	
Outer Shield Outer Shield Material:	
Outer Shield Material	
Unshielded	
Outer Jacket	
Outer Jacket Material:	
Outer Jacket Material	
PVC - Polyvinyl Chloride	
Outer Jacket Separator Thickness:	0.020 in.
Overall Cabling	
Overall Nominal Diameter:	0.160 x 0.320 in.
lechanical Characteristics (Overall)	
Operating Temperature Range:	-40°C To +70°C
Non-UL Temperature Rating:	70°C
Bulk Cable Weight:	27 lbs/1000 ft.
Max. Recommended Pulling Tension:	4 lbs.

Applicable Specifications and Agency Compliance (Overall) **Applicable Standards & Environmental Programs**

Detailed Specifications & Technical Data





9454 Coax - Dual Channel Audio Cable

EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Plenum/Non-Plenum	
Plenum (Y/N):	No
Electrical Characteristics (Overall)	
Nom. Characteristic Impedance:	
Impedance (Ohm) 110	
Nom. Capacitance Conductor to Shield:	
Capacitance (pF/ft)	
Nom. Conductor DC Resistance:	
DCR @ 20°C (Ohm/1000 ft)	
410.000	
Max. Operating Voltage - Non-UL:	
Voltage 90 V RMS	
Max. Recommended Current:	
Current	
0.3 Amps per conductor @ 25°C	
Notes (Overall)	
Notes: Stereo connecting cable.	
Related Documents:	
No related documents are available for this product	
Put Ups and Colors:	

Item #	Putup	Ship Weight	Color	Notes	Item Desc

Revision Date: 05-13-2011 **Revision Number: 1**

© 2011 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the action belief at the date of the product product before the product because a part is because a part of Their Disclosure is not for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



9454 Coax - Dual Channel Audio Cable

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.