



GPS Antenna Module

- GPS Active Antenna
- 17dB Gain
- High Sensitivity
- Low current consumption
- Additional MMCX Connector
- Suitable for embedded applications



ADA-12GD is a most compact GPS antenna module in the market. It's specially designed for the portable device that needs GPS antenna embedded such as PND, laptop, mobile phone and so on. Also, ADA-12 GD is compatible with most GPS receives available on the market and provides a perfect alternative for the application of the GPS in different fields.

Specification

Category	GPS	
Frequency	1575.42 ± 3 MHz	
Polarization	R.H.C.P.	
Antenna Gain	Typ. 1.0 dBic	
Bandwidth	5 MHz min @S11-10 dB.	
	LNA	
Amplifier Gain	Typ 17 dB	
Noise figure	Typ 1.5 dB	
Output Impedance	50 Ω	
VSWR	< 2.0:1	
	Electrical Specifications	
Supply Voltage	2.8 - 3.3 VDC	
Power consumption	6.2 mA (3.0 VDC)	
Total Gain	16 dB	
Impedance	50 Ω	
VSWR	< 2.0 : 1	
RF Cable	8 cm OD 1.13 + I-PEX(std)	
Connector	MMCX (Jack) (std)	
	Overall Performance	
GPS part size	13 x 19 x 6.25 mm	
Weight	5 ± 0.5 grams	
Mounting	Sticky tape	
Operating temperature	-40 — +85 ° C	
Storage temperature	-40 — +85 ° C	

Ordering codes

TYPE	Description	Comment
ADA-12GD	Cable Length and Connector	GPS antenna module

For the latest updates, visit our Web site: www.adactus.se

Disclaimer

Information furnished is believed to be accurate and reliable. However, Adactus assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Adactus reserves the right to make changes without further notice to any product herein to improve reliability, function or design. Adactus does not assume any liability arising out of the application or use of any product described herein.

This publication supersedes and replaces all information previously supplied. Adactus products are not authorized as critical components in life support devices or systems.