

Loctite 276

Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 6

sds no.: 303460

v003.0

Revision: 04.06.2010 printing date: 07.09.2011

1. Identification of the substance/preparation and of the company/undertaking

Trade name:

Loctite 276

Intended use:

Adhesive

Company name:

Henkel Limited

2 Bishop Square Business Park AL109EY Herfordshire Hatfield

Great Britain

Phone: +44 1606 593933 Fax-no.: +44 1606 863762

E-mail address of person responsible for Safety Data Sheet:

ua-products a fety. uk @uk.henkel.com

Emergency information:

24 Hours Emergency Tel: +44 (0)1442 278497

2. Hazards identification

R36/37/38 Irritating to eyes, respiratory system and skin. R43 May cause sensitisation by skin contact.

3. Composition / information on ingredients

General chemical description:

Anaerobic Sealant

Declaration of ingredients according to (EC) No 1907/2006:

MSDS-No.: 303460 Loctite 276 Page 2 of 6

V003.0

Hazardous components	EINECS	content	Classification
CAS-No.	ELINCS		
Hydroxypropyl methacrylate 27813-02-1	248-666-3	> 1 - < 5 %	Xi - Irritant; R36, R43
Acrylic acid	201-177-9	> 1 - < 5 %	Xn - Harmful; R20/21/22
79-10-7			R10
			C - Corrosive; R35
			N - Dangerous for the environment; R50
Cumene hydroperoxide	201-254-7	> 0,1 - < 0,9 %	T - Toxic; R23
80-15-9			Xn - Harmful; R21/22, R48/20/22
			O - Oxidizing; R7
			C - Corrosive; R34
			N - Dangerous for the environment; R51, R53
Cumene	202-704-5	> 0,1 -< 0,5 %	R10
98-82-8			Xn - Harmful; R65
			Xi - Irritant; R37
			N - Dangerous for the environment; R51, R53
3,3,5 Trimethylcyclohexyl	231-927-0	> 30 - < 40 %	Xi - Irritant; R36/37/38
methacrylate			
7779-31-9			
2-Hydroxyethyl methacrylate	212-782-2	> 10 - < 20 %	Xi - Irritant; R36/38
868-77-9			R43
Maleic acid	203-742-5	> 0,1 -< 0,9 %	Xn - Harmful; R22
110-16-7			Xi - Irritant; R36/37/38
			R43

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

4. First aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

5. Fire fighting measures

Suitable extinguishing media:

Carbon dioxide, foam, powder

Special protection equipment for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazardous combustion products:

Oxides of carbon, oxides of nitrogen, irritating organic vapors., Sulphur oxides

6. Accidental release measures

Personal precautions:

Avoid skin and eye contact.

Environmental precautions:

Do not let product enter drains.

MSDS-No.: 303460 Loctite 276 Page 3 of 6

V003.0

Clean-up methods:

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

7. Handling and storage

Handling:

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Storage:

Store in original containers at 8-21C (46.4-69.8F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

8. Exposure controls / personal protection

Components with specific control parameters for workplace:

Valid for

Great Britain

Basis

UK EH40 WELs

Ingredient	ppm	mg/m3	Type	Category	Remarks
CUMENE	25	125	Time Weighted Average		EH40 WEL
98-82-8			(TWA).		
CUMENE	50	250	Short Term Exposure		EH40 WEL
98-82-8			Limit (STEL):		
CUMENE			Skin designation:	Can be absorbed through the	EH40 WEL
98-82-8				skin.	
CUMENE			Skin designation:	Can be absorbed through the	ECTLV
98-82-8				skin.	
CUMENE	50	250	Short Term Exposure	Indicative	ECTLV
98-82-8			Limit (STEL):		
CUMENE	20	100	Time Weighted Average	Indicative	ECTLV
98-82-8			(TWA).		

Respiratory protection:

Use only in well-ventilated areas.

Hand protection:

The use of chemical resistant gloves such as Nitrile are recommended.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

General protection and hygiene measures:

Good industrial hygiene practices should be observed.

MSDS-No.: 303460 Loctite 276 Page 4 of 6

V003.0

9. Physical and chemical properties

General characteristics:

Appearance liquid Green
Odor: irritating

Phys./chem. properties:

VOC content <3 %

(1999/13/EC)

10. Stability and reactivity

Conditions to avoid:

Stable

Materials to avoid:

Reaction with strong acids. Reacts with strong oxidants.

11. Toxicological information

Oral toxicity:

May cause irritation to the digestive tract.

Inhalative toxicity:

Irritating to respiratory system

Skin irritation:

Irritating to the skin.

Eye irritation:

Irritating to eyes.

Sensitizing:

May cause sensitization by skin contact.

12. Ecological information

Ecotoxicity:

Hazardous components	Species	Exposure	Value	Value
CAS-No.		time	type	
Acrylic acid 79-10-7	Trout family (Salmonidae)	96 h	LC 50	27 mg/l
Cumene hydroperoxide	Ide, silver or golden orfe (Leuciscus idus)	48 h	LC 50	14 mg/l
80-15-9	Water flea (Daphnia magna)	24 h	EC 50	7 mg/l
Cumene hydroperoxide 80-15-9				
Cumene	Trout family (Salmonidae)	96 h	LC 50	4,8 mg/l
98-82-8				

General ecological information:

Do not empty into drains / surface water / ground water.

Precautions required with respect to Environmental Hazards of articles in which this product is used should be considered.

13. Disposal considerations

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

MSDS-No.: 303460 Loctite 276 Page 5 of 6

V003.0

Waste code(EWC):

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

14. Transport information

General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

15. Regulations - classification and identification

Indication of danger:

Xi - Irritant



Contains

2-Hydroxyethyl methacrylate, Hydroxypropyl methacrylate, Maleic acid

Risk phrases:

R36/37/38 Irritating to eyes, respiratory system and skin. R43 May cause sensitisation by skin contact.

Safety phrases:

S24/25 Avoid contact with skin and eyes.

S28 After contact with skin, wash immediately with plenty of water and soap. S37 Wear suitable gloves.

MSDS-No.: 303460 Loctite 276 Page 6 of 6

V003.0

16. Other information

The labelling of the product is indicated in Section 15. The full text of the R-phrases indicted by codes in this safety data sheet are as follows:

R10 Flammable.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R21/22 Harmful in contact with skin and if swallowed.

R22 Harmful if swallowed.

R23 Toxic by inhalation.

R34 Causes burns.

R35 Causes severe burns.

R36 Irritating to eyes.

R36/37/38 Irritating to eyes, respiratory system and skin.

R36/38 Irritating to eyes and skin.

R37 Irritating to respiratory system.

R43 May cause sensitisation by skin contact.

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R50 Very toxic to aquatic organisms.

R51 Toxic to aquatic organisms.

R53 May cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R7 May cause fire.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.