

## EVERBUILD NATURAL STONE SEALER



Colour	Product Code	Pack Size	Box Qty
Clear	STONE1	1Ltr	12

### Product Description

NATURAL STONE SEALER is a clear non hazardous solution which protects stone from staining from most liquids, hot cups, wine, coffee, tea, oil, soot, soil, foodstuffs etc. It is also an excellent repellent for chewing gum on most paving. NATURAL STONE SEALER can be used internally or externally on natural stone, masonry, cementitious substrates, grout, marble, terracotta, limestone, slate, brick and terrazzo, fireplace surrounds hearths, floor tiles, paving and worktops .NATURAL STONE SEALER will not discolour surfaces\*

### Benefits

- Solvent free formulation – non-flammable, low odour.
- Can be used internally or externally.
- Protects from accidental spillages i.e. wine, tea coffee etc.
- Dramatically improves water and mar resistance - High degree of water repellency in dried film.
- Does not alter appearance of surface to which it is applied.

### Areas For Use

- Seals and protects, paths, patios, natural stone, concrete and block paving from the effects of the sunlight, water, oil, petrol and fungal/moss growth.

### Limitations

- Use only as directed. Store only in original container.
- Do not use on surfaces which have been treated with silicone or stearate based water seals unless the surface is weathered enough so as to show no water beading effects.
- Do not use if rain is imminent (within 6 hours at 20°C).
- Do not apply below 5°C (air or surface temp).
- \* As quality of natural stone can vary, always test a small inconspicuous area for compatibility/discolouration prior to full scale application Do not use in applications where temperature exceeds 150°C as product will decompose above this temperature Always follow manufacturer's instructions carefully. As the company cannot be aware of all applications and materials its product may be used on, it is the user's responsibility to determine suitability for use. Please contact Technical Services for advice or request Technical Data Sheet.

### Surface Preparation

Ensure the surfaces to be treated are clean and free from any mould or fungal growth, waxes or coatings. Surfaces may be damp, but contain no standing water. Mask off surrounding areas to prevent contamination. Grouting must be allowed to dry for a minimum of 72 hours prior to application.

DO NOT APPLY TO HOT SURFACES OR IN STRONG DIRECT SUNLIGHT.

ALWAYS TEST A SMALL AREA FOR COMPATIBILITY PRIOR TO FULL SCALE APPLICATION

### Application

Apply by brush or roller (from suitable container) or suitable low pressure spray, ensuring an even distribution. Work well into surface for maximum penetration. DO NOT LEAVE SURPLUS MATERIAL ON THE SURFACE. If necessary, wipe up excess with a cloth dampened with STONE SEALER approximately 30 mins after application. Ensure an even and thorough coverage, especially on textured stone where "ponding" of the product must be avoided. Normally, only one coat is required, but for very porous stones, a second coat may be required, which must be applied approximately 30 minutes after first coat (i.e. before first coat is fully dry). Approximately 5-7 hours for foot traffic depending on air temperature. Open to vehicular traffic 48-72 hours after application. Do not apply below +5°C or above +35°C. Clean all tools etc with water before product dries. Aftercare: Areas treated with this product can be cleaned with warm water and detergent or EVERBUILD MOSS-AWAY

### Specific Data

Appearance	Clear solution
Specific Gravity @ 20°C	Approx 1.05 g/cm <sup>3</sup>
M.F.F.T	5°C
Application Temp	+5 to 35°C
Drying Time	5 -7 hours depending on conditions
Coverage	1 Litre will cover approximately 4 -8m <sup>2</sup> per coat depending on nature of surface.

### Health & Safety

Consult MSDS for full list of hazards.

### Storage

Store at moderate temperatures in original containers. PROTECT FROM FROST.

### Shelf Life

12 months from date of manufacture when stored according to manufacturers instructions.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given*



TECHNICAL DATA SHEET NO: NSS1  
PAGE: 3 OF 3

VERSION: 1-4/9/2009  
DATE OF ISSUE: 9/8/2011

---

*by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*