



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1. BRASS PER QQ-B-626
- 2. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 3. BERYLLIUM COPPER PER QQ-C-530
- 4. GOLD PL. 50 MIN THICK OVER NICKEL PL. 100 MIN THICK OVER COPPER STRIKE
- 5. TEFLON MIL-P-19468

DIMENSIONS ARE IN MILLIMETERS

UNLESS OTHERWISE SPECIFIED TOLERANCES  
 0.5-6 = ±0.2  
 6-30 = ±0.4  
 30-120 = ±0.6  
 120-315 = ±1  
 315-1000 = ±1.6  
 1000-2000 = ±2.4

PART NO.	SMA5071A1-3GT50G-50
APPROVED	DATE 10-11-01'
CHECKED	DATE 10-11-01'
DRAWN	DATE 10-11-01'

<b>Amphenol</b>	
TITLE SMA MALE TO FEMALE ADAPTOR	
DRAWING NO. KJ-SMA5071A1-3GT50G-50	
ITEM NO.	

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
6	CONTACT PIN	NOTE 3	NOTE 4	1	SMA5071A1-6
5	GASKET	SILICONE	RED	1	GS-6/43X06
4	RETAINER RING	NOTE 3	NATURAL	1	SMA5000-4-B
3	INSULATOR	NOTE 5	NATURAL	2	SMA5071A1-3T-50
2	BODY	NOTE 1	NOTE 2	1	SMA5071A1-2
1	SHELL	NOTE 1	NOTE 2	1	SMA5000-1-C

SCALE	5/1	ISSUE	A	FILE NO
-------	-----	-------	---	---------