




Precision Thin Film Chip Resistor Array ACAS06S0830371P1AT



FEATURE

- Product Information

REFERENCE

This unique special product is derived from the following underlying standard product:

- Precision Thin Film Chip Resistor Array
ACAS 0612 AT

This document is valid only in conjunction with the underlying standard product's data sheet in its most current edition:

- Precision Thin Film Chip Resistor Array
Superior Moisture Resistivity
Document No. 28770

CHARACTERIZATION

This Unique Special Product is characterized by the following facts:

The product definition meets the ranges published in the referenced data sheet:																																		
<input checked="" type="checkbox"/> COMPLETELY	<input type="checkbox"/> EXCEPT FOR: <table style="margin-left: 20px;"> <tr> <td>Temperature coefficient</td> <td></td> <td></td> </tr> <tr> <td>absolute</td> <td>=</td> <td>± 25ppm/K</td> </tr> <tr> <td>tracking</td> <td>=</td> <td>15ppm/K</td> </tr> <tr> <td>Tolerance on rated resistance</td> <td></td> <td></td> </tr> <tr> <td>absolute</td> <td>=</td> <td>± 0,25%</td> </tr> <tr> <td>matching</td> <td>=</td> <td>0,1%</td> </tr> <tr> <td colspan="3">Rated resistance values</td> </tr> <tr> <td></td> <td>R1 =</td> <td>4700 Ω</td> </tr> <tr> <td></td> <td>R2 =</td> <td>4700 Ω</td> </tr> <tr> <td></td> <td>R3 =</td> <td>4700 Ω</td> </tr> <tr> <td></td> <td>R4 =</td> <td>4700 Ω</td> </tr> </table>	Temperature coefficient			absolute	=	± 25ppm/K	tracking	=	15ppm/K	Tolerance on rated resistance			absolute	=	± 0,25%	matching	=	0,1%	Rated resistance values				R1 =	4700 Ω		R2 =	4700 Ω		R3 =	4700 Ω		R4 =	4700 Ω
	Temperature coefficient																																	
	absolute	=	± 25ppm/K																															
	tracking	=	15ppm/K																															
	Tolerance on rated resistance																																	
	absolute	=	± 0,25%																															
matching	=	0,1%																																
Rated resistance values																																		
	R1 =	4700 Ω																																
	R2 =	4700 Ω																																
	R3 =	4700 Ω																																
	R4 =	4700 Ω																																
Technology and manufacturing are identical to those used for the underlying product:																																		
<input checked="" type="checkbox"/> COMPLETELY	<input type="checkbox"/> EXCEPT FOR: —																																	
The choices of deliverable versions and packaging are identical to those for the underlying product:																																		
<input checked="" type="checkbox"/> COMPLETELY	<input type="checkbox"/> EXCEPT FOR: —																																	
The details published in the referenced data sheet under																																		
<ul style="list-style-type: none"> • Technical specification • Assembly apply to this product	<ul style="list-style-type: none"> • Dimensions • Functional performance • Description • Test and Requirements 																																	
<input checked="" type="checkbox"/> COMPLETELY	<input type="checkbox"/> EXCEPT FOR:																																	

ORDERING INFORMATION

Product description	ACAS 0612 4K7 E 4K7 AT P1
	ACAS 0612 4K7 E 4K7 AT P5
Part Number	ACASA4701E4701P5AT
	ACASA4701E4701P1AT