

# Technical data sheet · LÜTZE SUPERFLEX® PLUS N (C) PUR Motor/Power supply cable 0.6/1kV



PUR C-track cable · For the highest requirements

<b>Identification</b>	Type	(4×4)
	Part-No.	111462

## Use/Area of application

Application	<ul style="list-style-type: none"> <li>• Motor connection cable, special for frequency converters and SERVO drives</li> <li>• Through full PUR jacket and TPE / <b>HGI cable insulation</b> optimally suited for c-tracks, extremely harsh operating conditions, aggressive coolants and lubricants</li> <li>• For travel paths over 40 m, we recommend conductors with inside jacket</li> </ul>
Properties	<ul style="list-style-type: none"> <li>• High active and passive interference resistance (EMC)</li> <li>• Braided shield optimised for continuous flexible use</li> <li>• Very good alternating bending strength</li> <li>• Good pressure and roll-over resistance</li> <li>• Low adhesion, abrasion-proof, nick-resistant, tear-propagation-resistant</li> <li>• Hydrolisis-resistant, microbe-resistant, and rot-resistant</li> <li>• Weathering, ozone and UV resistant (normal lighting conditions)</li> <li>• Good us and salt water resistance</li> <li>• Excellent coolant and lubricant resistance</li> <li>• Widely resistant to oils, greases, alcohol-free benzines and kerosene (see tech. information)</li> <li>• Free from paint wetting disruptive substances (LABS-free), RoHS-compliant</li> </ul>

## Technical data

UL approval	1000 V 80 °C	
Voltage	U <sub>0</sub> /U	600/1000 V

23.11.2007 – Subject to technical modification

Part-No. 111462

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273  
Tel.: +1 (704) 504-0222 • Fax: +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3 Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs, B77 4DU  
Tel.: +44 (0)1827 31333-0 • Fax: +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk

# Technical data sheet · LÜTZE SUPERFLEX® PLUS N (C) PUR Motor/Power supply cable 0.6/1kV

	UL	1000 V
Test voltage	4000 V	
Insulation resistance	min. 100 MΩ × km	
Temperature range	moving	-25 °C to +80 °C
	fixed	-40 °C to +80 °C
Minimum bending radius	moving	Cable diameter × 10
	fixed	Cable diameter × 6
Radiation-resistance	5×10 <sup>7</sup> cJ/kg	
Burning behaviour	Flame-retardant according to VDE 0482 T 265; IEC 60332-1, UL VW-1; CSA FT 1	
Halogen-free	according to DIN EN 202641-1, EN 50267-2-1, EN 60684-2	
Number of strands/cross-section	(4×4)	
Outer-∅	11.1 approx. mm	
Weight	24.5 kg/100 m	
Cu-Index	18.8 kg/100 m	

## Design

Conductor structure	Bare copper wire, multi-strand according to DIN VDE 0295 or IEC 60228
Conductor insulation	Special TPE/HGI conductor insulation, UL qualified
Conductor labelling	Conductors black with white number print according to DIN EN 50334
Ground conductor	green/yellow according to DIN EN 50334
Stranding	Conductors twisted without mechanical stress, layer pitch optimised
Banding	Non-woven material over stranded cable
Inside jacket	TPE (optional)
Overall shield	Meshwork from tinned copper wire braid, optical covering ≥ 85 %
Outer jacket	Full polyurethane jacket, matt, adhesion-free surface
Jacket colour	orange RAL 2003; petrol RAL 5018 upon request

## General

Note	CE These products are in conformity to the EC Low Voltage Directive 73/23/EWG or 93/68/EWG respectively
------	---

## Logo



HGI insulation,  
low capacity

23.11.2007 – Subject to technical modification

Part-No. 111462

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273  
Tel.: +1 (704) 504-0222 • Fax: +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3 Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs, B77 4DU  
Tel.: +44 (0)1827 31333-0 • Fax: +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



**Technical data sheet · LÜTZE SUPERFLEX® PLUS N (C) PUR  
Motor/Power supply cable 0.6/1kV**

---

**halogenfree**

23.11.2007 – Subject to technical modification

Part-No. 111462

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273  
Tel.: +1 (704) 504-0222 • Fax: +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3 Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs, B77 4DU  
Tel.: +44 (0)1827 31333-0 • Fax: +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk