

Productname : GALVA'PACK MAT  
Ref.Nr.: BDS000469\_3\_20110908  
Creationdate : 08.09.11 Version : 1.0  
Replaces: AB39410

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**GALVA'PACK MAT**  
Aerosol

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Paints

**1.3. Details of the supplier of the safety data sheet**

**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele  
Belgium  
Tel.: +32(0)52/45.60.11  
Fax.: +32(0)52/45.00.34  
E-mail : hse@crcind.com

Subsidiaries		Tel	Fax
CRC Industries Finland Oy	Asemanrinne 13, 08500 Lohja as.	00358/(19)32.921	00358/(19)383.676
CRC Industries France	ZI du Val d'Argent B.P.90028, 12, Bld des Martyrs de Chateaubriant, 95102 Argenteuil Cedex	01.34.11.20.00	01.34.11.09.96
CRC Industries Deutschland GmbH	Südring 9, D-76473 Iffezheim	(07229) 303.0	(07229)30 32 66
CRC INDUSTRIES IBERIA S.L.U.	GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTRI. DE HONTORIA, 40195 SEGOVIA	0034/921.427.546	0034/921.436.270
CRC Industries Sweden	Kryptogatan 14, 431 53 Mölndal	0046/31 706 84 80	0046/31 27 39 91

**1.4. Emergency telephone number**

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to 67/548/EEC or 1999/45/EC:**



**Health:** R66: Repeated exposure may cause skin dryness or cracking.  
R67: Vapours may cause drowsiness and dizziness.  
**Physical:** EXTREMELY FLAMMABLE



Productname : GALVA'PACK MAT  
 Ref.Nr.: BDS000469\_3\_20110908  
 Creationdate : 08.09.11 Version : 1.0  
 Replaces: AB39410

**Environment:** R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 2.2. Label elements

<b>Warning symbol(s) :</b>	EXTREMELY FLAMMABLE  N : DANGEROUS FOR THE ENVIRONMENT 
<b>Risk-phrase(s) :</b>	R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R66: Repeated exposure may cause skin dryness or cracking. R67: Vapours may cause drowsiness and dizziness.
<b>Safety-phrase(s) :</b>	S2: Keep out of the reach of children. S16: Keep away from sources of ignition - No smoking. S23: Do not breathe vapours/spray. S35: This material and its container must be disposed of in a safe way. S51: Use only in well-ventilated areas.
<b>Extra label elements according to Aerosol Dispenser Directive 75/324/EC:</b>	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Without adequate ventilation formation of explosive mixtures may be possible.
<b>Other extra label elements:</b>	Remark: Preparations classified as harmful on the basis of an aspiration hazard need not be labelled as harmful with R65 when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment. (EU-Directive 67/548 Annex VI 9.4)

## 2.3. Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable.

### 3.2. Mixtures

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	symbol	R-phrases*	Notes
dimethyl ether	115-10-6	204-065-8	30-60	F+	12	A
zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3	10-30	N	50/53	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics,	-	921-024-6	5-10	F,Xn,N	11-38-51/53-65-67	
butanone; ethyl methyl ketone	78-93-3	201-159-0	5-10	F,Xi	11-36-66-67	A
zinc oxide	1314-13-2	215-222-5	1-5	N	50/53	B



**Productname :** GALVA'PACK MAT  
**Ref.Nr.:** BDS000469\_3\_20110908

**Creationdate :** 08.09.11 Version : 1.0  
**Replaces:** AB39410

Naphtha (petroleum), hydrotreated light	64742-49-0	265-151-9	1-5	Xn	65	B,P
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	265-185-4	1-5	Xn,N	10-51/53-65-66-67	B,P
butan-1-ol; n-butanol	71-36-3	200-751-6	<5	Xn	10-22-37/38-41-67	B
1,2,4-trimethylbenzene	95-63-6	202-436-9	<1	Xn,N	10-20-36/37/38-51/53	A
2-(3-heptyl)-N-butyl-1,3-oxazolane	165101-57-5	425-660-0	<1	N	R51/53	

**Explanation notes**

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit

P : not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7)

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
dimethyl ether		115-10-6	204-065-8	30-60	Flam. Gas 1,Press. Gas	H220	A
zinc powder - zinc dust (stabilized)		7440-66-6	231-175-3	10-30	Aquatic Acute 1,Aquatic Chronic 1	H400,H410	
butanone; ethyl methyl ketone		78-93-3	201-159-0	5-10	Flam. Liq. 2,Eye Irrit. 2,STOT SE 3	H225,H319,H336	A
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,	01-2119475514-35	-	921-024-6	5-10	Flam. Liq. 2,Skin Irrit. 2,STOT SE 3,Asp. Tox. 1,Aquatic Chronic 2	H225,H315,H336,H304,H411	
zinc oxide		1314-13-2	215-222-5	1-5	Aquatic Acute 1,Aquatic Chronic 1	H400,H410	B
butan-1-ol; n-butanol		71-36-3	200-751-6	<5	Flam. Liq. 3,Acute Tox. 4,STOT SE 3,Skin Irrit. 2,Eye Dam. 1,STOT SE 3	H226,H302,H335,H315,H318,H336	B
1,2,4-trimethylbenzene		95-63-6	202-436-9	<1	Flam. Liq. 3,Acute Tox. 4,Eye Irrit. 2,STOT SE 3,Skin Irrit. 2,Aquatic Chronic 2	H226,H332,H319,H335,H315,H411	A

**Explanation notes**

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit

(\* Explanation phrases : see chapter 16)

**SECTION 4: First aid measures****4.1. Description of first aid measures**

<b>Contact with eyes :</b>	If substance has got into eyes, immediately wash out with plenty of water Seek medical attention if irritation persists
<b>Contact with skin :</b>	Wash with water and soap. Seek medical attention if irritation persists
<b>Inhalation :</b>	Fresh air, keep warm and at rest. Seek medical attention if ill effects occur
<b>Ingestion :</b>	Ingestion is unlikely to occur If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

**4.2. Most important symptoms and effects, both acute and delayed**

**Inhalation :** Excessive inhalation of solvent vapours may give rise to nausea, headaches



**CRC Industries Europe bvba**

Touwslagerstraat 1, 9240 Zele – Belgium

Tel (+32) (0) 52 / 45 60 11 – Fax (+32) (0) 52 / 45 00 34 – www.crcind.com

**3 / 10**

**Productname :** GALVA'PACK MAT **Creationdate :** 08.09.11 Version : 1.0  
**Ref.Nr.:** BDS000469\_3\_20110908 **Replaces:** AB39410

<b>Ingestion :</b>	and dizziness After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms : sore throat, abdominal pain, nausea, vomiting
<b>Skin contact :</b>	May cause irritation. Symptoms : redness and pain
<b>Eye contact :</b>	May cause irritation. Symptoms : redness and pain

#### 4.3. Indication of any immediate medical attention and special treatment needed

**General Advice :** If you feel unwell, seek medical advice (show the label where possible)  
If symptoms persist always call a doctor

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

foam, carbon dioxide or dry agent

#### 5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C  
Forms hazardous decomposition products  
CO,CO2

#### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water  
In case of fire, do not breathe fumes

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources  
Ensure adequate ventilation  
Wear suitable protective clothing and gloves.

#### 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

#### 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

#### 6.4. Reference to other sections



Productname : GALVA'PACK MAT  
 Ref.Nr.: BDS000469\_3\_20110908  
 Creationdate : 08.09.11 Version : 1.0  
 Replaces: AB39410

For further information see section 8

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat and sources of ignition  
 Take precautionary measures against static discharges  
 Equipment should be earthed  
 Use explosion-proof electrical/ventilating/lighting/?/equipment.  
 Use only non-sparking tools.  
 Do not breathe aerosols or vapours.  
 Ensure adequate ventilation  
 Avoid contact with skin and eyes.  
 Wash thoroughly after use  
 Wear protective gloves/protective clothing/eye protection/face protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.  
 Keep out of reach of children.

### 7.3. Specific end use(s)

Paints

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits :

Hazardous ingredient	CAS-nr.	method	
<b>EU established exposure limits:</b>			
dimethyl ether	115-10-6	TWA	1000 ppm
butanone; ethyl methyl ketone	78-93-3	TWA	200 ppm
		STEL	300 ppm
1,2,4-trimethylbenzene	95-63-6	TWA	20 ppm
<b>National established exposure limits, United Kingdom</b>			
dimethyl ether	115-10-6	TWA	400 ppm
		STEL	500 ppm
butanone; ethyl methyl ketone	78-93-3	TWA	200 ppm
		STEL	300 ppm

### 8.2. Exposure controls



**Productname :** GALVA'PACK MAT  
**Ref.Nr.:** BDS000469\_3\_20110908  
**Creationdate :** 08.09.11 Version : 1.0  
**Replaces:** AB39410

**Control procedures :** Ensure adequate ventilation  
Keep away from heat and sources of ignition  
Take precautionary measures against static discharges

**Personal protection :** Take precautions to avoid contact with skin and eyes when handling the product.  
Ensure adequate ventilation

**inhalation :** In case of insufficient ventilation, wear suitable respiratory equipment.  
Air purifying respirator equipped with organic gas/vapor cartridge (type A or AX)

**hands and skin :** Wear suitable protective gloves

**eyes :** Wear safety goggles.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Apperance : physical state :** DME propelled liquid.  
**colour :** Grey.  
**odour :** Characteristic odor.  
**pH :** Not applicable.  
**Boiling point/range :** Not available.  
**Flash point :** < 0 °C  
**Evaporation rate :** Not available.  
**Explosion limits : upper limit :** Not available.  
**lower limit :** Not available.  
**Vapour pressure :** Not available.  
**Relative density :** 1.45 g/cm<sup>3</sup> (@ 20°C).  
**Solubility in water :** Insoluble in water  
**Auto-ignition :** > 200 °C

### 9.2. Other information

**VOC:** 640 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reactions known if used for its intended purpose

### 10.2. Chemical stability

Stable

### 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose



Productname : GALVA'PACK MAT  
 Ref.Nr.: BDS000469\_3\_20110908  
 Creationdate : 08.09.11 Version : 1.0  
 Replaces: AB39410

**10.4. Conditions to avoid**

Avoid overheating

**10.5. Incompatible materials**

Strong oxidising agent

**10.6. Hazardous decomposition products**

CO,CO2

**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

<b>Inhalation :</b>	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
<b>Ingestion :</b>	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
<b>Skin contact :</b>	Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis
<b>Eye contact :</b>	May cause irritation.

**Toxicological data :**

Hazardous ingredient	CAS-nr.	method	
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	LD50 oral rat	> 2000 mg/kg
butanone; ethyl methyl ketone	78-93-3	LD50 oral rat	>2000 mg/kg

**SECTION 12: Ecological information****12.1. Toxicity**

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Ecotoxicological data:**

Hazardous ingredient	CAS-nr.	method	
zinc oxide	1314-13-2	LC50 fish	1.1 mg/l
		EC50 daphnia	0.098 mg/l
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	IC50 algae	1 - 10 mg/l
		LC50 fish	10 - 100 mg/l
		EC50 daphnia	10 - 100 mg/l



**Productname :** GALVA'PACK MAT  
**Ref.Nr.:** BDS000469\_3\_20110908  
**Creationdate :** 08.09.11 Version : 1.0  
**Replaces:** AB39410

#### 12.2. Persistence and degradability

No experimental data available

#### 12.3. Bioaccumulative potential

No experimental data available

#### 12.4. Mobility in soil

Insoluble in water

#### 12.5. Results of PBT and vPvB assessment

No information available

#### 12.6. Other adverse effects

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**Product :** This material and its container must be disposed of in a safe way.  
Do not discharge into drains or the environment, dispose to an authorised waste collection point.  
**Contaminated packaging :** Disposal should be in accordance with local, state or national legislation

### SECTION 14: Transport information

#### 14.1. UN number

UN-number : 1950

#### 14.2. UN proper shipping name

Proper shipping name: AEROSOLS, flammable(Zinc)

#### 14.3. Transport hazard class(es)

Class: 2.1  
ADR/RID - Classification code: 5F

#### 14.4. Packing group

Packing group: Not applicable.





**Productname :** GALVA'PACK MAT  
**Ref.Nr.:** BDS000469\_3\_20110908  
**Creationdate :** 08.09.11 Version : 1.0  
**Replaces:** AB39410

#### 14.5. Environmental hazards

ADR/RID - Environmentally hazardous: Yes  
IMDG - Marine pollutant: Marine pollutant  
IATA/ICAO - Environmentally hazardous: Yes

#### 14.6. Special precautions for user

ADR/RID - Tunnelcode: (D)  
IMDG - Ems: F-D,S-U  
IATA/ICAO - PAX: 203  
IATA/ICAO - CAO: 203

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.  
Dir. 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.  
EU-directive 99/45/EC  
Regulation (EC) No 1907/2006 (REACH)

#### 15.2. Chemical safety assessment

No information available

### SECTION 16: Other information

\*Explanation risk-phrases:

- R10: Flammable.
- R11: Highly flammable.
- R12: Extremely flammable.
- R20: Harmful by inhalation.
- R22: Harmful if swallowed.
- R36: Irritating to eyes.
- R38: Irritating to skin.
- R41: Risk of serious damage to eyes.
- R65: Harmful: may cause lung damage if swallowed.
- R66: Repeated exposure may cause skin dryness or cracking.
- R67: Vapours may cause drowsiness and dizziness.
- R36/37/38: Irritating to eyes, respiratory system and skin.
- R37/38: Irritating to respiratory system and skin.
- R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



---

<b>Productname :</b>	GALVA'PACK MAT	<b>Creationdate :</b>	08.09.11 Version : 1.0
<b>Ref.Nr.:</b>	BDS000469_3_20110908	<b>Replaces:</b>	AB39410

---

R50/53

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

RR51/53

\*Explanation hazard statements:

- H220 : Extremely flammable gas.
- H225 : Highly flammable liquid and vapour.
- H226 : Flammable liquid and vapour.
- H302 : Harmful if swallowed.
- H304 : May be fatal if swallowed and enters airways.
- H315 : Causes skin irritation.
- H318 : Causes serious eye damage.
- H319 : Causes serious eye irritation.
- H332 : Harmful if inhaled.
- H335 : May cause respiratory irritation.
- H336 : May cause drowsiness or dizziness.
- H400 : Very toxic to aquatic life.
- H410 : Very toxic to aquatic life with long lasting effects.
- H411 : Toxic to aquatic life with long lasting effects.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

