



Features:

- Velcro Type with D Ring for size adjustment
- Double layers, conductive cup
- 3/4" Black velcro
- 2 pcs D-Ring
- 3/4" Elastic Strap

Open the buckle and velcro straps. Place the sole grounder on the bottom of the shoe. Close the toe strap by feeding the velcro through the plastic ring. Close the ankle strap. Place the ribbon inside the sock or shoe.

Notes:

Recommended to be worn on both feet.
The sole grounder must be tested from time to time using a footwear test station (093-0037).



Details	
Outer conductive surface (black)	$10^3 - 10^5 \Omega$
Inner anti-static surface (ivory)	$10^7 - 10^8 \Omega$
Conductive tab	$10^3 - 10^4 \Omega$
Resistance	1Meg resistor built in

Product Code:	Description:	Size (mm):	Additional Notes:
1812583	X-Large	175 x 228	Each (Ref: 068-0023)

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2011.