

Handheld Oscilloscope



Specifications

Feature	
Bandwidth	200 MHz
Rise time	≤ 1.8 ns
Real-time sampling rate	1 GS/s
Equivalent sampling range	25 GS/s
Vertical sensitivity	5 mV to 50 V / div
Record length (Maximum)	2 × 512 k
Scan time base	5 ns to 50 s / div
Trigger type	Edge, pulse, video and alternate
Automatic waveform measurements	27
Frequency counter	6 digits frequency counter
Ports	USB Host
Mathematics	Add, subtract, multiply, divide, reverse and FFT
Interface	Colour and mono display selectable
Power	The provided battery or out-sourced adaptor
Life of battery	3 hrs
Other features	Multimeter, special LCD copy feature
Multimeter	
Resistance	600 Ω / 6 M Ω / 60 M Ω : \pm (1.5% + 5 digits) 6 k Ω / 60 k Ω / 600 k Ω : \pm (1.2% + 5 digits)
DC Voltage	600 mV, 6 V, 60 V, 600 V, 1,000 V : \pm (1% + 5 digits)
AC Voltage (45 Hz to 400 Hz)	600 mV, 6 V, 60 V, 600 V, 700 V : \pm (1.2% + 5 digits), Frequency : < 200 Hz \pm (1.5% + 5 digits), Frequency : \geq 200 Hz

Handheld Oscilloscope



Specifications

Multimeter	
DC Current	6 mA, 60 mA, 600 mA : \pm (1.2% + 5 digits) 6 A : \pm (1.5% + 5 digits)
AC Current (45Hz to 400Hz)	6 mA, 60 mA, 600 mA : \pm (2% + 5 digits) 6 A : \pm (2.5% + 5 digits)
Capacitance	6 nF, 6 mF : \pm (5% + 10 digits) 60 nF, 600 nF, 6 μ F, 60 μ F, 600 μ F : \pm (4% + 5 digits)
Continuity buzzer	✓
Diode	
Trend diagram	
Testing mode	Manual / auto ranging
Maximum display	5,999

General Characteristics

Power	230 V ac (UK + Euro power adaptor)
LCD size	Diagonal 145 mm (5.7 inches)
Product colour	Grey + White
Product net weight	1.8 kg
Product size	268 × 168 × 60 mm
Accessories	Probe × 2 (1×, 10× switchable), Current voltage convertor × 2 (UT-M03, UT-M04) Power cord, DC adaptor and English manual, test lead
Standard individual packing	Tool box and gift box
Standard quantity per carton	4 pieces
Standard carton	475 × 460 × 380 mm (0.1 CBM per export carton)
Standard carton gross	Around 23.2 kg

Specifications and other information are subject to change without further notice

Part Number Table

Description	Part Number
Oscilloscope, Handheld DSO, 2CH, 200 MHZ	72-9365

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. TENMA™ is the registered trademark of the Group. © Premier Farnell plc 2011.