

# Grounding Connection Cord



## Specifications:

### Cord Construction and Material

The body housing shall contain a 10 mm female snap, with 1 meg ohm resistor, joined in series to the conductor with another 10 mm female snap on the other end, also with 1 meg ohm resistor. The ground end of the cord is moulded with single nylon material (strain relief / body housing)

Conductor : Diameter is 2.5 mm, with 7 tinsel wires

Insulation : Straight cord is insulated with polyurethane material

### Electrical Properties

The cord conductor shall have an end to end resistance not greater than 50 ohms

Resistivity : Current limiting resistance = 2 meg ohm  $\pm 20\%$

### Bending Life Test

Exceeds 20,000 cycles of bending life test without any physical damage on the strain relief

### Breakaway Force

1 to 5 lbs. of pull away force is required to disconnect the snap in a normal disconnect direction

### Connection Integrity

The tensile strength of the end connections shall be not less than 66% of the tensile strength of the wire, and in no case shall it be less than 5 lbs

### Colour

Straight cord available in yellow colour, moulded ends and chips in PMS340 green colour

### Hardware

All metal parts shall show no evidence of corrosion and rust after 24 hours submersion to salt solution. Preferably made from stainless steel or brass alloy plated with nickel

### Moulded Ends and Chips

Made of antistatic nylon material

## Part Number Table

Description	Part Number
Grounding Connection Cord, 2 M, 1 M ohm	28506

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2011.