

Soldering Station



Apply

Manufacturing production line
On field soldering jobs
Lead-free solder

Features:

- ESD safe - suitable for work on static-sensitive components
- Three programmable preset temperature buttons
- Easy to read white-on-blue LCD with temperature in °C or °F
- Temperature range : 150 to 450°C (302 to 842°F)
- On / Off switch on side of unit
- Includes soldering iron, stand, and sponge
- Additional range of soldering tips available
- New appearance design, big LCD screen, for clear and convenient reading
- PID power control loop with constant temperature set by MCU computer for more precision temperature control
- Imported temperature-beard materials with long life
- It is convenient that the device adopt three programmable knobs in different condition
- Display the temperature between Fahrenheit and Celsius flexibly, convenient for the type of operators
- Computerized temperature calibration can correct the difference between the actual and display temperature quickly
- Heating element malfunction alert

Specifications:

Input voltage	: 220 V ac (110 V optional)
Input frequency	: 50/60 Hz
Maximum power consumption	: 60 W
Temperature range	: 150 to 450°C
Tip and ground impedance	: < 2 Ω
Tip and ground potential	: < 5 mV
Heating element	: 2 cores, 60 W

Part Number Table

Description	Part Number
Soldering Station, Digital, ESD, EU	21-10115 EU
Soldering Station, Digital, ESD, UK	21-10115 UK

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. TENMA™ is the registered trademark of the Group. © Premier Farnell plc 2011.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk
www.mcmelectronics.com

