

Screened Cable



Specifications:

Voltage rating	: 440 V
Primary insulation material	: PVC
Secondary insulation material	: PVC
Secondary insulation colour	: Black
Conductor material	: Tinned Copper
Conductor make-up	: 7/0.2 mm
Current rating	: 1 A

Specification Table

Primary Screen Type	Standard	Number of Cores	Conductor Area CSA (mm ²)	External Diameter	Reel Length (m)	Temperature Range (°C)	Part Number
Tinned Annealed Copper Wire	DEF STAN 61-12 Part 4	4	0.22	4.6	100	70	7001186
Tinned Copper Braid	BS6746	12		6.8			7001136
Tinned Annealed Copper Wire	DEF STAN 61-12 Part 4	12		7.2	25		7004013
Tinned Copper Braid	BS6746	20		8.6	100		7010122
		36		10.7	25		7010126
Tinned Annealed Copper Wire	DEF STAN 61-12 Part 4			11.2	100		7004132

Dimensions : Millimetres (Unless Specified)

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2011.