



Technical Data Sheet

DEI De-ionised Water

Product Description

De-ionised water is ideal for small to medium quantity users of Safewash cleaning solutions, to give a final “polish” to circuit boards and assemblies which have been cleaned and rinsed in tap water.

DEI can be used in one of Electrolube’s “empty pumps or aerosols”, TSB or APB. TSB is a trigger spray with adjustable nozzle; APB is a container which allows an “aerosol” effect to be achieved by hand pumping the container to build up pressure.

It is not advisable to use DEI in a container and immerse the assembly or board, as DEI may quickly become contaminated with salts from tap water or even residues from the initial cleaning process.

Approvals:	RoHS Compliant (2002/95/EC)	Yes
Typical Properties:	Form:	Liquid
	Colour:	Colourless
	Specific Gravity (Density) @ 20°C:	1.00 g/ml
	Conductivity:	<3µS

<u>Packaging</u>	<u>Order Code</u>	<u>Shelf Life</u>
1 litre bulk	EDEI01L	36 months
5 litre bulk	EDEI05L	36 months

Directions for Use

Hold the PCB or assembly at approx. 45°. Spray DEI generously onto the assembly and allow to run down the board. The PCB may be quickly dried using Electrolube Airduster (EAD).

Copyright Electrolube 2011

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.